



## АСШнг 3x120+1x70-1 ТУ У 27.3-00214534-091:2017

Power cables with aluminium conductors, with impregnated paper insulation, lead-sheathed, with low-flammable PVC-compound protection hose

Cables are used for laying:

- *in dry premises (tunnels), ducts, cable cellars, mines, collectors, industrial and other premises, including damp, partially flooded premises, environment with medium and high corrosiveness*
- *with no risk of mechanical damage in operation*
- *in bunches*

Fire safety code in accordance with ДСТУ 4809:2007: ПБ1300000000

Products of this mark meet the requirements:

- *single wire cable flame retardance*
- *bunched cable flame retardance category B*

### TECHNICAL SPECIFICATIONS

|                                                                              |                 |                                     |
|------------------------------------------------------------------------------|-----------------|-------------------------------------|
| Rated voltage                                                                | kV              | 1                                   |
| Number and rated area of conductors                                          | mm <sup>2</sup> | 3 x 120 + 1 x 70                    |
| Insulation thickness between conductors                                      | mm              | 1.7                                 |
| Insulation thickness of conductor-sheath                                     | mm              | 1.45                                |
| Sheath thickness                                                             | mm              | 1.46                                |
| Permissible continuous current rating *                                      |                 |                                     |
| • <i>by aerial laying</i>                                                    | A               | 261                                 |
| • <i>by burial</i>                                                           | A               | 248                                 |
| Operating temperature range                                                  | °C              | -50 ... +50                         |
| Minimum bending radius by laying                                             | mm              | 630                                 |
| Level difference along the laying rout, not more than                        | m               | 20                                  |
| Metal sheath outer diameter (for reference only)                             | mm              | 36                                  |
| Rated outer diameter of the cable (for reference) **                         | mm              | 42                                  |
| Cable weight (approximate)                                                   | kg/km           | 3840                                |
| Rated factory cable length and gross weight of the delivery on the drums *** | m, t            | # 16a: 570 • 2.4<br># 18: 660 • 3.0 |

Notes:

*When ordering it is necessary to agree the factory length of the product with the manufacturer*


\* Long permissible current loads are calculated for the following conditions: air temperature plus 25 °C, soil temperature plus 15 °C, thermal resistivity of soil 1.2 °K·m/W, laying depth in the soil 0.7 m

\*\* The external diameter may differ from the rated up to ± 10 %



## АСШнг 3х120+1х70-1 ТУ У 27.3-00214534-091:2017

Power cables with aluminium conductors, with impregnated paper insulation, lead-sheathed, with low-flammable PVC-compound protection hose



### CONSTRUCTION

1. Aluminium multiwire compacted conductor
2. Impregnated paper insulation
3. Cable paper bundle
4. Belt insulation
5. Lead sheath
6. Pressed off low-flammable PVC compound protection hose

*Note: Conductor twisting is not illustrated*