



## АСБ 3x95(ож)-6 TY Y 27.3-00214534-091:2017

Power cables with aluminium conductors, with impregnated paper insulation, lead-sheathed, steel-tape armoured

Cables are used for laying:

- in soil (trenches) with medium corrosiveness without vagabond currents
- in soil (trenches) with low corrosiveness, as well as with vagabond currents
- in mines, non-hazardous as for gas and dust
- with a risk of mechanical damage and no tensile forces in operation

### TECHNICAL SPECIFICATIONS

|                                                                              |                 |                                     |
|------------------------------------------------------------------------------|-----------------|-------------------------------------|
| Rated voltage                                                                | kV              | 6                                   |
| Number and rated area of conductors                                          | mm <sup>2</sup> | 3 x 95                              |
| Insulation thickness between conductors                                      | mm              | 4                                   |
| Insulation thickness of conductor-sheath                                     | mm              | 2.95                                |
| Sheath thickness                                                             | mm              | 1.36                                |
| Permissible continuous current rating *                                      |                 |                                     |
| • by aerial laying                                                           | A               | 214                                 |
| • by burial                                                                  | A               | 213                                 |
| Operating temperature range                                                  | °C              | -50 ... +50                         |
| Minimum bending radius by laying                                             | mm              | 660                                 |
| Level difference along the laying rout, not more than                        | m               | 15                                  |
| Metal sheath outer diameter (for reference only)                             | mm              | 32                                  |
| Rated outer diameter of the cable (for reference) **                         | mm              | 44                                  |
| Cable weight (approximate)                                                   | kg/km           | 3940                                |
| Rated factory cable length and gross weight of the delivery on the drums *** | m, t            | # 16a: 520 • 2.3<br># 18: 600 • 2.8 |

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer


\* Long permissible current loads are calculated for the following conditions: air temperature plus 25 °C, soil temperature plus 15 °C, thermal resistivity of soil 1.2 °K·m/W, laying depth in the soil 0.7 m

\*\* The external diameter may differ from the rated up to ± 10 %



## АСБ 3х95(ож)-6 ТУ У 27.3-00214534-091:2017

Power cables with aluminium conductors, with impregnated paper insulation, lead-sheathed, steel-tape armoured



### CONSTRUCTION

1. Aluminium conductor
2. Impregnated paper insulation
3. Cable paper bundle
4. Belt insulation
5. Conducting paper screen
6. Lead sheath
7. Bedding
8. Double steel-tape armour
9. Outer covering

*Note: Conductor twisting is not illustrated*