

**АСБВШнг 3х120-1**  
**ТУ У 27.3-00214534-091:2017**

Power cables with aluminium conductors, with impregnated paper insulation, lead-sheathed, steel-tape armoured, with low-flammable PVC-compound protection hose

Cables are used for laying:

- *in dry premises (tunnels), ducts, cable cellars, mines, collectors, industrial and other premises, including damp, partially flooded premises, environment with medium and high corrosiveness*
- *in fire-risk premises*
- *on special cable bridges*
- *with a risk of mechanical damage and no tensile forces in operation*
- *in bunches*

Fire safety code in accordance with ДСТУ 4809:2007: ПБ120000000

Products of this mark meet the requirements:

- *single wire cable flame retardance*
- *bunched cable flame retardance category A*

**TECHNICAL SPECIFICATIONS**

|                                                                              |                 |                                     |
|------------------------------------------------------------------------------|-----------------|-------------------------------------|
| Rated voltage                                                                | kV              | 1                                   |
| Number and rated area of conductors                                          | mm <sup>2</sup> | 3 x 120                             |
| Insulation thickness between conductors                                      | mm              | 1.7                                 |
| Insulation thickness of conductor-sheath                                     | mm              | 1.45                                |
| Sheath thickness                                                             | mm              | 1.42                                |
| Permissible continuous current rating *                                      |                 |                                     |
| • <i>by aerial laying</i>                                                    | A               | 261                                 |
| • <i>by burial</i>                                                           | A               | 248                                 |
| Operating temperature range                                                  | °C              | -50 ... +50                         |
| Minimum bending radius by laying                                             | mm              | 690                                 |
| Level difference along the laying route, not more than                       | m               | 25                                  |
| Metal sheath outer diameter (for reference only)                             | mm              | 31                                  |
| Rated outer diameter of the cable (for reference) **                         | mm              | 46                                  |
| Cable weight (approximate)                                                   | kg/km           | 4250                                |
| Rated factory cable length and gross weight of the delivery on the drums *** | m, t            | # 16a: 480 • 2.3<br># 18: 550 • 2.8 |

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer


\* Long permissible current loads are calculated for the following conditions: air temperature plus 25 °C, soil temperature plus 15 °C, thermal resistivity of soil 1.2 °K·m/W, laying depth in the soil 0.7 m

\*\* The external diameter may differ from the rated up to ± 10 %



## АСБВШнг 3х120-1 ТУ У 27.3-00214534-091:2017

Power cables with aluminium conductors, with impregnated paper insulation, lead-sheathed, steel-tape armoured, with low-flammable PVC-compound protection hose



### CONSTRUCTION

1. Aluminium multiwire compacted conductor
2. Impregnated paper insulation
3. Belt insulation
4. Lead sheath
5. Bedding with PVC compound moulded-in hose
6. Double galvanized steel-tape armour
7. Pressed off low-flammable PVC compound protection hose

*Note: Conductor twisting is not illustrated*