



## **ПвВГнгд-FR 5x70-1 ТУ У 31.3-00214534-055:2006**

Fire resistant power cables with copper conductors, XLPE-insulated, with low fire-risk PVC-compound outer sheath

---

Cables are used for laying:

- *in bunches*
  - *in premises, dry ducts and tunnels, in corrosive environment*
  - *in bunches, in crowded places*
  - *power supply cable lines of NPP safety system equipment, circuits wiring of fire safety systems (fire alarm circuits, power supply of fire-fighting pumps, lightning of emergency exits and evacuation routes, smoke exhaust and blowing ventilation systems, evacuation elevators); for wiring in hospital surgical wings, emergency and equipment (current collectors) power supply circuits, operating in a fire emergency*
- 

Manufacturing of extruded fire-resistant barrier is possible

---

Fire safety code in accordance with ДСТУ 4809:2007: ПБ123121080

Products of this mark meet the requirements:

- *single wire cable flame retardance*
- *bunched cable flame retardance category A*
- *toxicity class Tk3 of the combustion products of nonmetallic elements (toxicity index over 120 g/m<sup>3</sup>)*
- *class ДТк1 on smoke-forming ability by smouldering of non-metallic elements (coefficient of smoke formation from 50 to 500 m<sup>2</sup>/kg)*
- *class ДПк2 on smoke-forming ability by combustion (minimum luminous flux more than 60 %)*
- *corrosive class Кк1 of combustion products of non-metallic elements (the number of halogen hydrides less than 150 mg/g, pH less than 4.3, specific conductivity more than 10 μS/mm)*
- *flame-resistant class FE180 under fire conditions with a temperature not less than 750 °C*



## ПВГнгд-FR 5x70-1 ТУ У 31.3-00214534-055:2006

Fire resistant power cables with copper conductors, XLPE-insulated, with low fire-risk PVC-compound outer sheath

### TECHNICAL SPECIFICATIONS

Rated voltage	kV	1
Number and rated area of conductors	mm <sup>2</sup>	5 x 70
Phase insulation thickness	mm	1.1
Permissible continuous current rating (AC of industrial frequency) *		
• by aerial laying	A	246
• by burial	A	235
Maximum permissible conductor temperature		
• Continuous	°C	+90
• in emergency operation	°C	+130
• at short circuit	°C	+250
Operating temperature range	°C	-50 ... +50
Minimum bending radius by laying	mm	337.5
Rated outer diameter of the cable (for reference) **	mm	45
Cable weight (approximate)	kg/km	4520
Rated factory cable length and gross weight of the delivery on the drums ***	m, t	# 16a: 480 • 2.4 # 18: 550 • 2.9 # 20: 870 • 4.6

#### Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

\* Long permissible current loads are calculated for the following conditions: air temperature plus 25 °C, soil temperature plus 15 °C, thermal resistivity of soil 1.2 °K·m/W, laying depth in the soil 0.7 m

\*\* The external diameter may differ from the rated up to ± 10 %

### CONSTRUCTION

1. Copper multiwire compact conductor
2. Fire-resistant barrier  
*Note: Manufacturing of extruded fire-resistant barrier is possible*
3. XLPE insulation
4. Low fire-risk PVC-compound bundle
5. Low fire-risk PVC-compound inner sheath
6. Low fire-risk PVC compound outer sheath

*Note: Conductor twisting is not illustrated*

