

## СИП-5нг 4x70+2x35 ТУ У 31.3-00214534-014-2002

Self-supporting flame-retardant wires with polymer compound insulation

Used for laying:

- *aerial electric power lines for the rated voltage of 0.6/1 kV*
- *branches to the inputs into dwellings and outbuildings*

Fire safety code in accordance with ДСТУ 4809:2007: ПБ100000000

Products of this mark meet the requirements:

- *single wire cable flame retardance*

### TECHNICAL SPECIFICATIONS


|                                                                              |                 |                                                         |
|------------------------------------------------------------------------------|-----------------|---------------------------------------------------------|
| Rated voltage                                                                | kV              | 0.6 / 1                                                 |
| Number and rated area of phase conductors                                    | mm <sup>2</sup> | 4 x 70                                                  |
| Number and rated area of additional conductors for light circuits            | mm <sup>2</sup> | 2 x 35                                                  |
| Phase insulation thickness                                                   | mm              | 1.5                                                     |
| Current ratings *                                                            |                 |                                                         |
| • <i>Continuous</i>                                                          | A               | 240                                                     |
| • <i>at short circuit (not more than 1 s)</i>                                | kA              | 6.5                                                     |
| Maximum permissible conductor temperature                                    |                 |                                                         |
| • <i>Continuous</i>                                                          | °C              | +90                                                     |
| • <i>at short circuit (not more than 5 s)</i>                                | °C              | +250                                                    |
| Operating temperature range                                                  | °C              | -60 ... +50                                             |
| Permissible temperature of laying (installation), no less than               | °C              | -20                                                     |
| Minimum bending radius by laying                                             | mm              | 380                                                     |
| Rated outer diameter of the cable (for reference) **                         | mm              | 38                                                      |
| Weight (approximate)                                                         | kg/km           | 1190                                                    |
| Rated factory cable length and gross weight of the delivery on the drums *** | m, t            | # 16a: 700 • 1.1<br># 18: 800 • 1.4<br># 20: 1280 • 2.2 |

Notes:

*When ordering it is necessary to agree the factory length of the product with the manufacturer*

\* Long permissible current loads are calculated for the following conditions: ambient temperature plus 25 °C, wind speed 0.6 m/s, the intensity of solar radiation 1000 W/m<sup>2</sup>

\*\* The external diameter may differ from the rated up to ± 10 %



## СИП-5нг 4x70+2x35 ТУ У 31.3-00214534-014-2002

Self-supporting flame-retardant wires with polymer compound insulation

### CONSTRUCTION

1. Aluminium multiwire compacted conductor
2. Multiwire compacted aluminium assisting conductor for light circuits
3. Flame-retardant polymer compound insulation

*Note: Wire lay-up is not illustrated.*

