7, Autogennaya Str., Kharkov, 61099, Ukraine. Phone: (+38-057) 728-1244, 728-1241. Fax: (+38-057) 728-1243, (+38-0572) 946-830
E-mail: market@yuzhcable.com.ua

200301-351095000000

# СИП-3-35 1х95
# ДСТУ 4743:2007, ТУ У 27.3-00214534-066:2013

Single-core self-supporting high-voltage wires with light-stabilized cross-linked polyethylene insulation

Used for laying:

- *aerial electric power lines for the rated voltage from 10 kV till 35 kV*
- *in air, types II and III according to ГОСТ 15150-69, including on sea coasts, salt lakes, in industrial areas and areas of saline sands*

It is possible to manufacture the wire with longitudinal core sealing by water-blocking materials

## TECHNICAL SPECIFICATIONS

| | | |
|---|---|---|
| Rated voltage | kV | 35 |
| Number and rated area of phase conductors | $mm^2$ | 1 x 95 |
| Phase insulation thikness | mm | 3.5 |
| Current ratings * | | |
| • *Continious* | A | 400 |
| • *at short circuit (not more than 1 s)* | kA | 8.2 |
| Maximum permissible conductor temperature | | |
| • *Continious* | °C | +90 |
| • *at short circuit (not more than 5 s)* | °C | +250 |
| Operating temperature range | °C | -60 ... +50 |
| Permissible temperature of laying (installation), no less than | °C | -20 |
| Minimum bending radius by laying | mm | 186 |
| Rated outer diameter of the cable (for reference) ** | mm | 18.6 |
| Weight (approximate) | kg/km | 420 |
| Rated factory cable length and gross weight of the delivery on the drums *** | m, t | # 16a: 3120 • 1.6<br># 18: 3570 • 2.0<br># 20: 5710 • 3.0 |

*Notes:*

*When ordering it is neccesary to agree the factory length of the product with the manufacturer*

** Long permissible current loads are calculated for the following conditions: ambient temperature plus 25 °C, wind speed 0.6 m/s, the intensity of solar radiation 1000 $W/m^2$*

*** The external diameter may differ from the rated up to ± 10 %*

© 2024 PJSC Yuzhcable Works. © 2024 A. Kevorkyan

7, Autogennaya Str., Kharkov, 61099, Ukraine. Phone: (+38-057) 728-1244, 728-1241. Fax: (+38-057) 728-1243, (+38-0572) 946-830
E-mail: market@yuzhcable.com.ua

200301-351095000000

# СИП-3-35 1х95
# ДСТУ 4743:2007, ТУ У 27.3-00214534-066:2013

Single-core self-supporting high-voltage wires with light-stabilized cross-linked polyethylene insulation

## CONSTRUCTION

*1. Multiwire aluminium-alloy compacted conductor*
*Note: It is possible to manufacture the wire with longitudinal core sealing by water-blocking materials*

*2. Light-stabilized cross-linked polyethylene insulation*

© 2024 PJSC Yuzhcable Works. © 2024 A. Kevorkyan