

**СБВГ 27x0.9**  
**ТУ У 31.3-00214534-008-2001**

Signal blocking cables with copper conductors, with polyethylene insulation, in PVC compound sheath

Designed for electrical installations of railway signaling, centralization, blocking and automation at a rated voltage of 380 V AC at frequency 50 Hz or 700 V DC

Cables are used for laying:

- *single laying*
- *in premises, dry ducts and tunnels, in corrosive environment*
- *in the absence of mechanical effects on cable*

Manufacturing of cables with core diameter of 0.8 mm is possible

Fire safety code in accordance with ДСТУ 4809:2007: ПБ100000000

Products of this mark meet the requirements:

- *single wire cable flame retardance*

**TECHNICAL SPECIFICATIONS**

|                                                                              |        |                  |
|------------------------------------------------------------------------------|--------|------------------|
| Rated voltage                                                                | V      | 380 / 700        |
| Number and rated diameter of conductors                                      | mm     | 27 x 0.9         |
| Electrical resistance of the conductor at 20 °C                              | Ohm/km | 23.3             |
| Operating capacity, not more than                                            | nF/km  | 150.0            |
| Operating temperature range                                                  | °C     | -50 ... +60      |
| Minimum bending radius by laying                                             | mm     | 105              |
| Cable outer diameter (for reference only) **                                 | mm     | 15               |
| Cable weight (approximate)                                                   | kg/km  | 308              |
| Rated factory cable length and gross weight of the delivery on the drums *** | m, t   | # 12: 1450 • 0.6 |

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

\*\* The external diameter may differ from the rated up to  $\pm 10\%$



## СБВГ 27х0.9 ТУ У 31.3-00214534-008-2001

Signal blocking cables with copper conductors, with polyethylene insulation, in PVC compound sheath

### CONSTRUCTION

#### 1. Copper conductor

*Note: Manufacturing of cables with core diameter of 0.8 mm is possible*

#### 2. Polyethylene insulation

#### 3. PET film winding

#### 4. PVC compound sheath

*Note: Conductor twisting is not illustrated*

