



## **СБВГнг 3x0.9 ТУ У 31.3-00214534-008-2001**

Signal blocking cables with copper conductors, with polyethylene insulation, in low flammable PVC compound sheath

Designed for electrical installations of railway signaling, centralization, blocking and automation at a rated voltage of 380 V AC at frequency 50 Hz or 700 V DC

Cables are used for laying:

- *in bunches*
- *in premises, dry ducts and tunnels, in corrosive environment*
- *in the absence of mechanical effects on cable*

Manufacturing of cables with core diameter of 0.8 mm is possible

Fire safety code in accordance with ДСТУ 4809:2007: ПБ121000000

Products of this mark meet the requirements:

- *single wire cable flame retardance*
- *bunched cable flame retardance category A*
- *toxicity class Tk1 of the combustion products of nonmetallic elements (toxicity index from 13 up to 40 g/m<sup>3</sup>)*


### **TECHNICAL SPECIFICATIONS**

|   |        |             |
|---|--------|-------------|
| Rated voltage                                   | V      | 380 / 700   |
| Number and rated diameter of conductors         | mm     | 3 x 0.9     |
| Electrical resistance of the conductor at 20 °C | Ohm/km | 23.3        |
| Operating capacity, not more than               | nF/km  | 150.0       |
| Operating temperature range                     | °C     | -40 ... +60 |
| Minimum bending radius by laying                | mm     | 49          |
| Cable outer diameter (for reference only) **    | mm     | 7           |
| Cable weight (approximate)                      | kg/km  | 63          |

Notes:


*When ordering it is necessary to agree the factory length of the product with the manufacturer*

*\*\* The external diameter may differ from the rated up to ± 10 %*



## СБВГнг 3x0.9 ТУ У 31.3-00214534-008-2001

Signal blocking cables with copper conductors, with polyethylene insulation, in low flammable PVC compound sheath



### CONSTRUCTION

#### 1. Copper conductor

*Note: Manufacturing of cables with core diameter of 0.8 mm is possible*

#### 2. Polyethylene insulation

#### 3. PET film winding

#### 4. Low flammable PVC compound sheath

*Note: Conductor twisting is not illustrated*