



СБПАШп 10x2x1 ТУ У 31.3-00214534-008-2001

Signal blocking cables with copper conductors, with polyethylene insulation, in aluminium sheath, in polyethylene hose

Designed for electrical installations of railway signaling, centralization, blocking and automation at a rated voltage of 380 V AC at frequency 50 Hz or 700 V DC

Cables are used for laying:

- *in soil*
- *at external electrical influences*
- *in the absence of mechanical effects on cable*

TECHNICAL SPECIFICATIONS

| | | |
|---|--------|------------------|
| Rated voltage | V | 380 / 700 |
| Number of pairs and nominal conductor diameter | | 10 x 1 |
| Electrical resistance of the conductor at 20 °C | Ohm/km | 28.8 |
| Operating capacity, not more than | nF/km | 100.0 |
| Attenuation coefficient of pairs at a temperature of 20 °C, not more than | dB/km | 0.94 |
| Coupling losses on near-end of cable between any pairs over a length of 300 m, not less than: | | |
| • <i>for 100% of the values</i> | dB | 60.0 |
| • <i>for 80% of the values</i> | dB | 62.0 |
| Protective action coefficient of aluminium sheath at longitudinal EMF of 30 V/ km, not more than: | | 0.7 |
| Operating temperature range | °C | -50 ... +60 |
| Minimum bending radius by laying | mm | 168 |
| Cable outer diameter (for reference only) ** | mm | 24 |
| Cable weight (approximate) | kg/km | 626 |
| Rated factory cable length and gross weight of the delivery on the drums | m, t | # 14: 1090 • 0.9 |

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

*** The external diameter may differ from the rated up to ± 10 %*



СБПАШп 10x2x1 ТУ У 31.3-00214534-008-2001

Signal blocking cables with copper conductors, with polyethylene insulation, in aluminium sheath, in polyethylene hose

CONSTRUCTION

1. Copper conductor
2. Polyethylene insulation
3. PET film winding
4. Polyethylene inner sheath
5. Paper core wrapping
6. Aluminium sheath
7. Polyethylene protection hose

Note: Pair twisting in the layer of core on the picture not shown.

