



СБЗПАШп 27x2x0.9 ТУ У 31.3-00214534-008-2001

Signal blocking cables with copper conductors, with polyethylene insulation, with water-blocking core filling, in aluminium sheath, in polyethylene hose

Designed for electrical installations of railway signaling, centralization, blocking and automation at a rated voltage of 380 V AC at frequency 50 Hz or 700 V DC

Cables are used for laying:

- *in soil*
- *in conditions of excessive humidity*
- *at external electrical influences*
- *in the absence of mechanical effects on cable*


TECHNICAL SPECIFICATIONS

| | | |
|---|--------|-------------------------------------|
| Rated voltage | V | 380 / 700 |
| Number of pairs and nominal conductor diameter | | 27 x 0.9 |
| Electrical resistance of the conductor at 20 °C | Ohm/km | 28.8 |
| Operating capacity, not more than | nF/km | 100.0 |
| Attenuation coefficient of pairs at a temperature of 20 °C, not more than | dB/km | 1.04 |
| Coupling losses on near-end of cable between any pairs over a length of 300 m, not less than: | | |
| • <i>for 100% of the values</i> | dB | 60.0 |
| • <i>for 80% of the values</i> | dB | 62.0 |
| Protective action coefficient of aluminium sheath at longitudinal EMF of 30 V/ km, not more than: | | 0.7 |
| Operating temperature range | °C | -50 ... +60 |
| Minimum bending radius by laying | mm | 217 |
| Cable outer diameter (for reference only) ** | mm | 31 |
| Cable weight (approximate) | kg/km | 1147 |
| Rated factory cable length and gross weight of the delivery on the drums | m, t | # 14: 610 • 0.9 # 16a: 990 • 1.4 |

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

*** The external diameter may differ from the rated up to ± 10 %*



СБЗПАШп 27x2x0.9 ТУ У 31.3-00214534-008-2001

Signal blocking cables with copper conductors, with polyethylene insulation, with water-blocking core filling, in aluminium sheath, in polyethylene hose

CONSTRUCTION

1. Copper conductor
2. Polyethylene insulation
3. PET film lapping with water-blocking filling
4. Polyethylene inner sheath
5. Paper core wrapping
6. Aluminium sheath
7. Polyethylene protection hose

Note: Pair twisting in the layer of core on the picture not shown.

