



KГВ 1x1.5 ТУ У 31.3-00214534-006-2001

Power flexible cables with copper conductors, PVC compound insulation, outer PVC compound sheath

Cables for connecting of moveable devices to the power network for rated voltage of 660 V, frequency up to 400 Hz or constant voltage of 1000 V

Fire safety code in accordance with ДСТУ 4809:2007: ПБ100000000

Products of this mark meet the requirements:

- *single wire cable flame retardance*

TECHNICAL SPECIFICATIONS

| | | |
|--|-----------------|-------------|
| Rated voltage | kV | 0.66 |
| Number and rated area of conductors | mm ² | 1 x 1.5 |
| Insulation thickness | mm | 0.7 |
| Permissible continious current rating * | | |
| • <i>by aerial laying (AC of industrial frequency) *</i> | A | 22 |
| • <i>by aerial laying (DC) *</i> | A | 29 |
| Operating temperature range | °C | -50 ... +70 |
| Flexibility class acc. to GOST 22483-77 | | 5 |
| Minimum bending radius by laying | mm | 48 |
| Rated outer diameter of the cable (for reference) ** | mm | 6 |
| Cable weight (approximate) | kg/km | 50 |

Notes:

When ordering it is neccessary to agree the factory length of the product with the manufacturer

* Long permissible current loads are calculated for the air temperature plus 25 °C

** The external diameter may differ from the rated up to ± 10 %

CONSTRUCTION

1. Copper multiwire conductor
2. PVC compound insulation
3. PVC compound outer sheath

