

## **NYM-O 3x2.5**

### **DIN VDE 0250-204**

Power cables with copper conductors, PVC compound insulation, outer PVC compound sheath

Cable technical specifications conform DIN VDE 0250 p.204

Cables are used for:

- *electric wiring and cable lines installation in industrial, residential and public buildings and facilities*
- *laying over the plaster, inside and under plaster, in brick masonry and concrete, in pipes and ducts*
- *outdoor installation, if protected from sun rays*

Manufacturing of cables with light-stabilized outer sheath is possible

Fire safety code in accordance with ДСТУ 4809:2007: ПБ1000000000

Products of this mark meet the requirements:

- *single wire cable flame retardance*

## **TECHNICAL SPECIFICATIONS**


|                                                          |                 |             |
|----------------------------------------------------------|-----------------|-------------|
| Rated voltage                                            | kV              | 0.66        |
| Number and rated area of conductors                      | mm <sup>2</sup> | 3 x 2.5     |
| Insulation thickness                                     | mm              | 0.7         |
| Permissible continious current rating *                  |                 |             |
| • <i>by aerial laying (AC of industrial frequency) *</i> | A               | 27          |
| Operating temperature range                              | °C              | -50 ... +50 |
| Minimum bending radius by laying                         | mm              | 40          |
| Rated outer diameter of the cable (for reference) **     | mm              | 10          |
| Cable weight (approximate)                               | kg/km           | 180         |

Notes:

*When ordering it is necessary to agree the factory length of the product with the manufacturer*

*\* Long permissible current loads are calculated for the air temperature plus 25 °C*

*\*\* The external diameter may differ from the rated up to ± 10 %*



## **NYM-O 3x2.5** **DIN VDE 0250-204**

Power cables with copper conductors, PVC compound insulation, outer PVC compound sheath

### **CONSTRUCTION**

1. Copper conductor
2. PVC compound insulation
3. Extruded uncured stock inner sheath
4. PVC compound outer sheath

*Note: Manufacturing of cables with light-stabilized outer sheath is possible*

*Note: Conductor twisting is not illustrated*

