

## Micro Tube 432 \* (36x12)-2.7 TY Y 27.3-00214534-116:2019

Fiber optic distribution cables of micro-tube construction with HDPE sheath

### Mark formation:

Micro Tube 432[c](36x12)-2.7

[c] type of optical fiber

- A – single-mode with extended wavelength band (ITU-T G.652D, ITU-T G.657A1)
- D - single-mode, not sensitive to losses on macro-bending (ITU-T G.657A2)

Order placing: sample of indication

Micro Tube 432A(36x12)-2.7

Cable construction provides fast access to micro-tubes and fibres (no tools required), minimum of sealing compound and avoiding the risk of micro-tube kinking

Cables are used for:

- for digital signal transmission in optic local networks as distribution cables
- for compact outdoor installation in PE ducts by pulling or floating techniques


### TECHNICAL SPECIFICATIONS

Number of optical micro-tube in cable		36
Number of optical fibers in cable	units	432
Permissible tensile force (short-term)	N	2700
Permissible tensile force (continuous)	N	1350
Permissible crushing force, no less than	N/10 sm	1500
Ambient temperature		
• during operation	°C	-30 ... +70
• during storage and transportation	°C	-30 ... +70
• during laying and installation	°C	-10 ... +40
Cable weight (approximate)	kg/km	185
Rated outer diameter of the cable (for reference) **	mm	15.2
Minimum bending radius during laying	mm	304
Minimum bending radius during operation	mm	152

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

\*\* The external diameter may differ from the rated up to  $\pm 10\%$



## Micro Tube 432 \* (36x12)-2.7 TY Y 27.3-00214534-116:2019

Fiber optic distribution cables of micro-tube construction with HDPE sheath

### CONSTRUCTION

1. Fiberglass rod in sheath
2. Water-blocking thread
3. Optic fibers
4. Tube of fiber optic micromodule
5. Aramid-thread or glass-thread layer
6. Lapping layer of water-blocking tape
7. HDPE outer sheath

Note: Optical module twisting is not illustrated.

