

**ААШВ 3х95(ож)-1**  
**ТУ У 27.3-00214534-091:2017**

Power cables with aluminium conductors, with impregnated paper insulation, aluminium-sheathed, with PVC-compound protection hose

Cables are used for laying:

- *in soil (trenches) with high corrosiveness without vagabond currents*
- *in soil (trenches) with medium corrosiveness, as well as with vagabond currents*
- *in dry premises (tunnels), ducts, cable cellars, mines, collectors, industrial and other premises, including damp, partially flooded premises, environment with medium and high corrosiveness*
- *in fire-risk premises*
- *on special cable bridges*
- *on bridges*
- *in mines, non-hazardous as for gas and dust*
- *with no risk of mechanical damage in operation*

Fire safety code in accordance with ДСТУ 4809:2007: ПБ100000000

Products of this mark meet the requirements:

- *single wire cable flame retardance*

**TECHNICAL SPECIFICATIONS**


|  |                 |                 |
|--|-----------------|-----------------|
| Rated voltage  | kV              | 1               |
| Number and rated area of conductors  | mm <sup>2</sup> | 3 x 95          |
| Insulation thickness between conductors                                      | mm              | 1.5             |
| Insulation thickness of conductor-sheath                                     | mm              | 1.25            |
| Sheath thickness   | mm              | 1.3             |
| Permissible continuous current rating *                                      |                 |                 |
| • <i>by aerial laying</i>  | A               | 218             |
| • <i>by burial</i>   | A               | 219             |
| Operating temperature range  | °C              | -50 ... +50     |
| Minimum bending radius by laying   | mm              | 775             |
| Level difference along the laying rout, not more than                        | m               | 25              |
| Metal sheath outer diameter (for reference only)                             | mm              | 26              |
| Rated outer diameter of the cable (for reference) **                         | mm              | 31              |
| Cable weight (approximate)   | kg/km           | 1560            |
| Rated factory cable length and gross weight of the delivery on the drums *** | m, t            | # 16: 370 • 0.8 |

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer


\* Long permissible current loads are calculated for the following conditions: air temperature plus 25 °C, soil temperature plus 15 °C, thermal resistivity of soil 1.2 °K·m/W, laying depth in the soil 0.7 m

\*\* The external diameter may differ from the rated up to ± 10 %



## **ААШВ 3х95(ож)-1** **ТУ У 27.3-00214534-091:2017**

Power cables with aluminium conductors, with impregnated paper insulation, aluminium-sheathed, with PVC-compound protection hose



### **CONSTRUCTION**

1. *Aluminium conductor*
2. *Impregnated paper insulation*
3. *Belt insulation*
4. *Aluminium sheath*
5. *Pressed PVC compound protection hose*

*Note: Conductor twisting is not illustrated*