





АСШв 3х185(ож)-1 ТУ У 27.3-00214534-091:2017



Power cables with aluminium conductors, with impregnated paper insulation, lead-sheathed, with PVC-compound protection hose

Cables are used for laying:

- in dry premises (tunnels), ducts, cable cellars, mines, collectors, industrial and other premises, including damp, partially flooded premises, environment with medium and high corrosivenes
- · with no risk of mechanical damage in operation

Fire safety code in accordance with ДСТУ 4809:2007: ΠБ100000000

Products of this mark meet the requirements:

· single wire cable flame retardance

## **TECHNICAL SPECIFICATIONS**

Rated voltage	kV	1
Number and rated area of conductors	mm²	3 x 185
Insulation thikness between conductors	mm	1.9
Insulation thikness of conductor-sheath	mm	1.55
Sheath thikness	mm	1.42
Permissible continious current rating *		
by aerial laying	Α	342
• by burial	Α	314
Operating temperature range	°C	-50 +50
Minimum bending radius by laying	mm	630
Level difference along the laying rout, not more than	m	20
Metal shaeth outer diameter (for reference only)	mm	35
Rated outer diameter of the cable (for reference) **	mm	42
Cable weight (approximate)	kg/km	4050
Rated factory cable length and gross weight of the delivery	m, t	# 16a: 570 • 2.6
on the drums ***		# 18: 660 • 3.1

## Notes:

When ordering it is neccesary to agree the factory length of the product with the manufacturer

<sup>\*</sup> Long permissible current loads are calculated for the following conditions: air temperature plus 25 °C, soil temperature plus 15 °C, thermal resistivity of soil 1.2 °K • m/W, laying depth in the soil 0.7 m

<sup>\*\*</sup> The external diameter may differ from the rated up to  $\pm$  10 %



ТУ У 27.3-00214534-091:2017






АСШв 3х185(ож)-1



Power cables with aluminium conductors, with impregnated paper insulation, lead-sheathed, with PVC-compound protection hose



## CONSTRUCTION

- 1. Aluminium conductor
- 2. Impregnated paper insulation
- 3. Cable paper bundle
- 4. Belt insulation
- 5. Lead sheath
- 6. Pressed PVC compound protection hose

Note: Conductor twisting is not illustrated