



## АСБ2л 4x185-1 ТУ У 27.3-00214534-091:2017

Power cables with aluminium conductors, with impregnated paper insulation, lead-sheathed, steel-tape armoured

Cables are used for laying:

- *in soil (trenches) with high corrosiveness, as well as with vagabond currents*
- *with a risk of mechanical damage and no tensile forces in operation*

### TECHNICAL SPECIFICATIONS

|  |                 |                                    |
|--|-----------------|------------------------------------|
| Rated voltage  | kV              | 1                                  |
| Number and rated area of conductors  | mm <sup>2</sup> | 4 x 185                            |
| Insulation thickness between conductors                                      | mm              | 1.9                                |
| Insulation thickness of conductor-sheath                                     | mm              | 1.55                               |
| Sheath thickness   | mm              | 1.62                               |
| Permissible continuous current rating *                                      |                 |                                    |
| • <i>by aerial laying</i>  | A               | 318                                |
| • <i>by burial</i>   | A               | 292                                |
| Operating temperature range  | °C              | -50 ... +50                        |
| Minimum bending radius by laying   | mm              | 855                                |
| Level difference along the laying rout, not more than                        | m               | 25                                 |
| Metal sheath outer diameter (for reference only)                             | mm              | 45                                 |
| Rated outer diameter of the cable (for reference) **                         | mm              | 57                                 |
| Cable weight (approximate)   | kg/km           | 6820                               |
| Rated factory cable length and gross weight of the delivery on the drums *** | m, t            | # 18: 340 • 2.8<br># 20: 550 • 4.4 |

Notes:

*When ordering it is necessary to agree the factory length of the product with the manufacturer*


*\* Long permissible current loads are calculated during operation in four-wire networks with load in all the conductors for the following conditions: air temperature plus 25 °C, soil temperature plus 15 °C, thermal resistivity of soil 1.2 °K·m/W, laying depth in the soil 0.7 m*

*\*\* The external diameter may differ from the rated up to ± 10 %*



**АСБ2л 4x185-1**  
**ТУ У 27.3-00214534-091:2017**

Power cables with aluminium conductors, with impregnated paper insulation, lead-sheathed, steel-tape armoured



**CONSTRUCTION**

1. Aluminium multiwire compacted conductor
2. Impregnated paper insulation
3. Cable paper bundle
4. Belt insulation
5. Lead sheath
6. Double-layer plastic-tape bedding
7. Double steel-tape armour
8. Outer covering

*Note: Conductor twisting is not illustrated*