



## ЦАББ2л 3x150-6 TY Y 27.3-00214534-091:2017

Power cables with aluminium conductors, with non-draining impregnated paper insulation, lead-sheathed, steel-tape armoured

Cables are used for laying:

- *without level difference limitation*
- *in soil (trenches) with high corrosiveness, as well as with vagabond currents*
- *with a risk of mechanical damage and no tensile forces in operation*

### TECHNICAL SPECIFICATIONS

|  |                 |  |
|--|-----------------|--|
| Rated voltage  | kV              | 6  |
| Number and rated area of conductors                                      | mm <sup>2</sup> | 3 x 150  |
| Insulation thickness between conductors                                  | mm              | 4  |
| Insulation thickness of conductor-sheath                                 | mm              | 2.95   |
| Sheath thickness   | mm              | 1.52   |
| Permissible continuous current rating *                                  |                 |  |
| • <i>by aerial laying</i>  | A               | 285  |
| • <i>by burial</i>   | A               | 275  |
| Operating temperature range  | °C              | -50 ... +50  |
| Minimum bending radius by laying   | mm              | 780  |
| Metal sheath outer diameter (for reference only)                         | mm              | 39   |
| Rated outer diameter of the cable (for reference) **                     | mm              | 52   |
| Cable weight (approximate)   | kg/km           | 5660   |
| Rated factory cable length and gross weight of the delivery on the drums | m, t            | # 16a: 370 • 2.4<br># 18: 430 • 2.9<br># 20: 680 • 4.5 |

Notes:

*When ordering it is necessary to agree the factory length of the product with the manufacturer*


*\* Long permissible current loads are calculated for the following conditions: air temperature plus 25 °C, soil temperature plus 15 °C, thermal resistivity of soil 1.2 °K·m/W, laying depth in the soil 0.7 m*

*\*\* The external diameter may differ from the rated up to ± 10 %*



## ЦАБ2л 3x150-6 ТУ У 27.3-00214534-091:2017

Power cables with aluminium conductors, with non-draining impregnated paper insulation, lead-sheathed, steel-tape armoured



### CONSTRUCTION

1. Aluminium multiwire compacted conductor
2. Impregnated paper insulation
3. Cable paper bundle
4. Belt insulation
5. Conducting paper screen
6. Lead sheath
7. Double-layer plastic-tape bedding
8. Double steel-tape armour
9. Outer covering

Note: Conductor twisting is not illustrated