





7, Autogennaya Str., Kharkov, 61099, Ukraine. Phone: (+38-057) 728-1244, 728-1241. Fax: (+38-057) 728-1243, (+38-0572) 946-830 E-mail: market@yuzhcable.com.ua

# АСБлГ 1х240-3 ТУ У 27.3-00214534-091:2017

Power cables with aluminium conductors, with impregnated paper insulation, lead-sheathed, steel-tape armoured

Cables are used for laying:

- in dry premises (tunnels), ducts, cable cellars, mines, collectors, industrial and other premises, including damp, partially flooded premises, environment with medium and high corrosivenes
- in fire-risk premises
- · on technological trestles
- · on special cable bridges
- · with a risk of mechanical damage and no tensile forces in operation

Fire safety code in accordance with ДСТУ 4809:2007: ПБ10000000

Products of this mark meet the requirements:

· single wire cable flame retardance

### **TECHNICAL SPECIFICATIONS**

| Rated voltage   | kV    | 3               |
|---|-------|-----------------|
| Number and rated area of conductors                         | mm²   | 1 x 240         |
| Insulation thikness of conductor-sheath                     | mm    | 2.1             |
| Sheath thikness   | mm    | 1.21            |
| Permissible continious direct current rating *              |       |                 |
| by aerial laying  | Α     | 604             |
| • by burial   | Α     | 496             |
| Operating temperature range                                 | °C    | -50 +50         |
| Minimum bending radius by laying                            | mm    | 775             |
| Level difference along the laying rout, not more than       | m     | 25              |
| Metal shaeth outer diameter (for reference only)            | mm    | 25              |
| Rated outer diameter of the cable (for reference) **        | mm    | 31              |
| Cable weight (approximate)                                  | kg/km | 2420            |
| Rated factory cable length and gross weight of the delivery | m, t  | # 16: 370 • 1.2 |
| on the drums ***  |       |                 |

#### Notes:

When ordering it is neccesary to agree the factory length of the product with the manufacturer

<sup>\*</sup> Long permissible current loads are calculated for the following conditions: air temperature plus 25 °C, soil temperature plus 15 °C, thermal resistivity of soil 1.2 °K • m/W, laying depth in the soil 0.7 m

<sup>\*\*</sup> The external diameter may differ from the rated up to  $\pm$  10 %







7, Autogennaya Str., Kharkov, 61099, Ukraine. Phone: (+38-057) 728-1244, 728-1241. Fax: (+38-057) 728-1243, (+38-0572) 946-830 E-mail: market@yuzhcable.com.ua

## АСБлГ 1х240-3 ТУ У 27.3-00214534-091:2017

Power cables with aluminium conductors, with impregnated paper insulation, lead-sheathed, steel-tape armoured



### **CONSTRUCTION**

- 1. Aluminium multiwire compacted conductor
- 2. Impregnated paper insulation
- 3. Lead sheath
- 4. Single-layer plastic-tape bedding
- 5. Double galvanized steel-tape armour