



## АСБнлШнг 3х95(ож)-10 ТУ У 27.3-00214534-091:2017

Power cables with aluminium conductors, with impregnated paper insulation, lead-sheathed, steel-tape armoured, with low-flammable PVC-compound protection hose

Cables are used for laying:

- in fire-risk premises
- on special cable bridges
- with a risk of mechanical damage and no tensile forces in operation
- in bunches

Fire safety code in accordance with ДСТУ 4809:2007: ПБ120000000

Products of this mark meet the requirements:

- single wire cable flame retardance
- bunched cable flame retardance category A

### TECHNICAL SPECIFICATIONS

|  |                 |                                     |
|--|-----------------|-------------------------------------|
| Rated voltage  | kV              | 10                                  |
| Number and rated area of conductors                                      | mm <sup>2</sup> | 3 x 95                              |
| Insulation thickness between conductors                                  | mm              | 5.5                                 |
| Insulation thickness of conductor-sheath                                 | mm              | 4                                   |
| Sheath thickness   | mm              | 1.46                                |
| Permissible continuous current rating *                                  |                 |                                     |
| • by aerial laying   | A               | 194                                 |
| • by burial  | A               | 192                                 |
| Operating temperature range  | °C              | -50 ... +50                         |
| Minimum bending radius by laying   | mm              | 735                                 |
| Level difference along the laying rout, not more than                    | m               | 15                                  |
| Metal sheath outer diameter (for reference only)                         | mm              | 36                                  |
| Rated outer diameter of the cable (for reference) **                     | mm              | 49                                  |
| Cable weight (approximate)   | kg/km           | 4910                                |
| Rated factory cable length and gross weight of the delivery on the drums | m, t            | # 16a: 410 • 2.3<br># 18: 460 • 2.7 |

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

\* Long permissible current loads are calculated for the following conditions: air temperature plus 25 °C, soil temperature plus 15 °C, thermal resistivity of soil 1.2 °K·m/W, laying depth in the soil 0.7 m


\*\* The external diameter may differ from the rated up to ± 10 %



## АСБнлШнг 3х95(ож)-10 ТУ У 27.3-00214534-091:2017

Power cables with aluminium conductors, with impregnated paper insulation, lead-sheathed, steel-tape armoured, with low-flammable PVC-compound protection hose

### CONSTRUCTION



1. Aluminium conductor
2. Impregnated paper insulation
3. Cable paper bundle
4. Belt insulation
5. Conducting paper screen
6. Lead sheath
7. Plastic-tape and glass-tape bedding
8. Double galvanized steel-tape armour
9. Pressed off low-flammable PVC compound protection hose

Note: Conductor twisting is not illustrated