**СГ 3x50(ож)-1**
ТУ У 27.3-00214534-091:2017

Power cables with copper conductors, with impregnated paper insulation, lead-sheathed

Cables are used for laying:

- *in blocks*
- *with no risk of mechanical damage in operation*

Fire safety code in accordance with ДСТУ 4809:2007: ПБ100000000

Products of this mark meet the requirements:

- *single wire cable flame retardance*

TECHNICAL SPECIFICATIONS


| | | |
|--|-----------------|-----------------|
| Rated voltage | kV | 1 |
| Number and rated area of conductors | mm ² | 3 x 50 |
| Insulation thickness between conductors | mm | 1.5 |
| Insulation thickness of conductor-sheath | mm | 1.25 |
| Sheath thickness | mm | 1.5 |
| Permissible continious current rating * | | |
| • <i>by aerial laying</i> | A | 195 |
| • <i>by burial</i> | A | 200 |
| Operating temperature range | °C | -50 ... +50 |
| Minimum bending radius by laying | mm | 315 |
| Level difference along the laying rout, not more than | m | 20 |
| Metal shaeth outer diameter (for reference only) | mm | 20 |
| Rated outer diameter of the cable (for reference) ** | mm | 21 |
| Cable weight (approximate) | kg/km | 2390 |
| Rated factory cable length and gross weight of the delivery on the drums *** | m, t | # 16: 790 • 2.2 |

Notes:

When ordering it is neccesary to agree the factory length of the product with the manufacturer


** Long permissible current loads are calculated for the following conditions: air temperature plus 25 °C, soil temperature plus 15 °C, thermal resistivity of soil 1.2 °K·m/W, laying depth in the soil 0.7 m*

*** The external diameter may differ from the rated up to ± 10 %*



СГ 3x50(ож)-1
ТУ У 27.3-00214534-091:2017

Power cables with copper conductors, with impregnated paper insulation, lead-sheathed



CONSTRUCTION

1. Copper conductor
2. Impregnated paper insulation
3. Belt insulation
4. Lead sheath

Note: Conductor twisting is not illustrated