

## СГ 3x70-6 TY Y 27.3-00214534-091:2017

Power cables with copper conductors, with impregnated paper insulation, lead-sheathed

Cables are used for laying:

- *in blocks*
- *with no risk of mechanical damage in operation*

Fire safety code in accordance with ДСТУ 4809:2007: ПБ100000000

Products of this mark meet the requirements:

- *single wire cable flame retardance*

### TECHNICAL SPECIFICATIONS


|  |                 |                 |
|--|-----------------|-----------------|
| Rated voltage  | kV              | 6               |
| Number and rated area of conductors  | mm <sup>2</sup> | 3 x 70          |
| Insulation thickness between conductors                                      | mm              | 4               |
| Insulation thickness of conductor-sheath                                     | mm              | 2.95            |
| Sheath thickness   | mm              | 1.81            |
| Permissible continuous current rating *                                      |                 |                 |
| • <i>by aerial laying</i>  | A               | 244             |
| • <i>by burial</i>   | A               | 236             |
| Operating temperature range  | °C              | -50 ... +50     |
| Minimum bending radius by laying   | mm              | 495             |
| Level difference along the laying rout, not more than                        | m               | 15              |
| Metal sheath outer diameter (for reference only)                             | mm              | 32              |
| Rated outer diameter of the cable (for reference) **                         | mm              | 33              |
| Cable weight (approximate)   | kg/km           | 4250            |
| Rated factory cable length and gross weight of the delivery on the drums *** | m, t            | # 16: 330 • 1.7 |

Notes:

*When ordering it is necessary to agree the factory length of the product with the manufacturer*

\* Long permissible current loads are calculated for the following conditions: air temperature plus 25 °C, soil temperature plus 15 °C, thermal resistivity of soil 1.2 °K·m/W, laying depth in the soil 0.7 m

\*\* The external diameter may differ from the rated up to ± 10 %



**СГ 3x70-6**  
**ТУ У 27.3-00214534-091:2017**

Power cables with copper conductors, with impregnated paper insulation, lead-sheathed

**CONSTRUCTION**

1. Copper multiwire compact conductor
2. Impregnated paper insulation
3. Cable paper bundle
4. Belt insulation
5. Conducting paper screen
6. Lead sheath

*Note: Conductor twisting is not illustrated*

