

**ЦСБВШнг 3х50(ож)-6**  
**ТУ У 27.3-00214534-091:2017**

Power cables with copper conductors, with non-draining impregnated paper insulation, lead-sheathed, steel-tape armoured, with low-flammable PVC-compound protection hose

Cables are used for laying:

- *without level difference limitation*
- *in dry premises (tunnels), ducts, cable cellars, mines, collectors, industrial and other premises, including damp, partially flooded premises, environment with medium and high corrosiveness*
- *in fire-risk premises*
- *on special cable bridges*
- *with a risk of mechanical damage and no tensile forces in operation*
- *in bunches*

Fire safety code in accordance with ДСТУ 4809:2007: ПБ120000000

Products of this mark meet the requirements:

- *single wire cable flame retardance*
- *bunched cable flame retardance category A*

**TECHNICAL SPECIFICATIONS**


|  |                 |                  |
|--|-----------------|------------------|
| Rated voltage  | kV              | 6                |
| Number and rated area of conductors  | mm <sup>2</sup> | 3 x 50           |
| Insulation thickness between conductors                                      | mm              | 4                |
| Insulation thickness of conductor-sheath                                     | mm              | 2.95             |
| Sheath thickness   | mm              | 1.26             |
| Permissible continuous current rating *                                      |                 |                  |
| • <i>by aerial laying</i>  | A               | 200              |
| • <i>by burial</i>   | A               | 197              |
| Operating temperature range  | °C              | -50 ... +50      |
| Minimum bending radius by laying   | mm              | 585              |
| Metal sheath outer diameter (for reference only)                             | mm              | 26               |
| Rated outer diameter of the cable (for reference) **                         | mm              | 39               |
| Cable weight (approximate)   | kg/km           | 4160             |
| Rated factory cable length and gross weight of the delivery on the drums *** | m, t            | # 16a: 630 • 2.9 |

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

\* Long permissible current loads are calculated for the following conditions: air temperature plus 25 °C, soil temperature plus 15 °C, thermal resistivity of soil 1.2 °K·m/W, laying depth in the soil 0.7 m


\*\* The external diameter may differ from the rated up to ± 10 %



## ЦБВШнг 3x50(ож)-6 ТУ У 27.3-00214534-091:2017

Power cables with copper conductors, with non-draining impregnated paper insulation, lead-sheathed, steel-tape armoured, with low-flammable PVC-compound protection hose

### CONSTRUCTION



1. Copper conductor
2. Impregnated paper insulation
3. Cable paper bundle
4. Belt insulation
5. Conducting paper screen
6. Lead sheath
7. Bedding with PVC compound moulded-in hose
8. Double galvanized steel-tape armour
9. Pressed off low-flammable PVC compound protection hose

*Note: Conductor twisting is not illustrated*