



## ЦСБГ 3x70-6 ТУ У 27.3-00214534-091:2017

Power cables with copper conductors, with non-draining impregnated paper insulation, lead-sheathed, steel-tape armoured

Cables are used for laying:

- without level difference limitation
- in dry premises (tunnels), ducts, cable cellars, mines, collectors, industrial and other premises, including damp, partially flooded premises, environment with medium and high corrosiveness
- in fire-risk premises
- on technological trestles
- on special cable bridges
- with a risk of mechanical damage and no tensile forces in operation

Fire safety code in accordance with ДСТУ 4809:2007: ПБ100000000

Products of this mark meet the requirements:

- single wire cable flame retardance

### TECHNICAL SPECIFICATIONS

|  |                 |                  |
|--|-----------------|------------------|
| Rated voltage  | kV              | 6                |
| Number and rated area of conductors                                      | mm <sup>2</sup> | 3 x 70           |
| Insulation thickness between conductors                                  | mm              | 4                |
| Insulation thickness of conductor-sheath                                 | mm              | 2.95             |
| Sheath thickness   | mm              | 1.36             |
| Permissible continuous current rating *                                  |                 |                  |
| • by aerial laying   | A               | 244              |
| • by burial  | A               | 236              |
| Operating temperature range  | °C              | -50 ... +50      |
| Minimum bending radius by laying   | mm              | 570              |
| Metal sheath outer diameter (for reference only)                         | mm              | 32               |
| Rated outer diameter of the cable (for reference) **                     | mm              | 38               |
| Cable weight (approximate)   | kg/km           | 4730             |
| Rated factory cable length and gross weight of the delivery on the drums | m, t            | # 16a: 700 • 3.6 |

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer


\* Long permissible current loads are calculated for the following conditions: air temperature plus 25 °C, soil temperature plus 15 °C, thermal resistivity of soil 1.2 °K·m/W, laying depth in the soil 0.7 m

\*\* The external diameter may differ from the rated up to ± 10 %



## ЦСБГ 3x70-6 ТУ У 27.3-00214534-091:2017

Power cables with copper conductors, with non-draining impregnated paper insulation, lead-sheathed, steel-tape armoured



### CONSTRUCTION

1. Copper multiwire compact conductor
2. Impregnated paper insulation
3. Cable paper bundle
4. Belt insulation
5. Conducting paper screen
6. Lead sheath
7. Double galvanized steel-tape armour

Note: Conductor twisting is not illustrated