



## **ПВБ6ШВ 3x2.5+1x1.5-1** **ТУ У 31.3-00214534-048:2007**

Power cables with copper conductors, XLPE-insulated, galvanized steel-tape armoured, with PVC-compound protection hose

Cables are used for laying:

- *single laying*
- *in premises, dry ducts and tunnels, in corrosive environment*
- *in places, where small mechanical impacts on cable are possible, including tensile forces*

Manufacturing of non-galvanized armoured cable, covered with a layer of bitumen and PET film is possible

Fire safety code in accordance with ДСТУ 4809:2007: ПБ100000000

Products of this mark meet the requirements:

- *single wire cable flame retardance*

### **TECHNICAL SPECIFICATIONS**

|                                                                              |                 |                   |
|------------------------------------------------------------------------------|-----------------|-------------------|
| Rated voltage                                                                | kV              | 1                 |
| Number and rated area of conductors                                          | mm <sup>2</sup> | 3 x 2.5 + 1 x 1.5 |
| Phase insulation thickness                                                   | mm              | 0.7               |
| Permissible continuous current rating (AC of industrial frequency) *         |                 |                   |
| • <i>by aerial laying</i>                                                    | A               | 34                |
| • <i>by burial</i>                                                           | A               | 40                |
| Maximum permissible conductor temperature                                    |                 |                   |
| • <i>Continuous</i>                                                          | °C              | +90               |
| • <i>in emergency operation</i>                                              | °C              | +130              |
| • <i>at short circuit</i>                                                    | °C              | +250              |
| Operating temperature range                                                  | °C              | -50 ... +50       |
| Minimum bending radius by laying                                             | mm              | 135               |
| Rated outer diameter of the cable (for reference) **                         | mm              | 18                |
| Cable weight (approximate)                                                   | kg/km           | 430               |
| Rated factory cable length and gross weight of the delivery on the drums *** | m, t            | # 12: 1010 • 0.5  |

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer


\* Long permissible current loads are calculated for the following conditions: air temperature plus 25 °C, soil temperature plus 15 °C, thermal resistivity of soil 1.2 °K·m/W, laying depth in the soil 0.7 m

\*\* The external diameter may differ from the rated up to ± 10 %



**ПвБ6Шв 3x2.5+1x1.5-1**  
**ТУ У 31.3-00214534-048:2007**

Power cables with copper conductors, XLPE-insulated, galvanized steel-tape armoured, with PVC-compound protection hose



## CONSTRUCTION

1. Copper conductor
2. XLPE insulation
3. PET film winding
4. PVC compound belt insulation
5. Double galvanized steel-tape armour
6. Pressed PVC compound protection hose

*Note: Conductor twisting is not illustrated*