



**СИП-5 1x25**  
**ТУ У 31.3-00214534-014-2002**

Self-supporting wires with light-stabilized cross-linked polyethylene insulation

Used for laying:

- aerial electric power lines for the rated voltage of 0.6/1 kV
- branches to the inputs into dwellings and outbuildings

**TECHNICAL SPECIFICATIONS**

Rated voltage	kV	0.6 / 1
Number and rated area of phase conductors	mm <sup>2</sup>	1 x 25
Phase insulation thickness	mm	1.3
Current ratings *		
• Continuous	A	130
• at short circuit (not more than 1 s)	kA	2.3
Maximum permissible conductor temperature		
• Continuous	°C	+90
• at short circuit (not more than 5 s)	°C	+250
Operating temperature range	°C	-60 ... +50
Permissible temperature of laying (installation), no less than	°C	-20
Minimum bending radius by laying	mm	85
Rated outer diameter of the cable (for reference) **	mm	8.5
Weight (approximate)	kg/km	100

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

\* Long permissible current loads are calculated for the following conditions: ambient temperature plus 25 °C, wind speed 0.6 m/s, the intensity of solar radiation 1000 W/m<sup>2</sup>

\*\* The external diameter may differ from the rated up to ± 10 %

**CONSTRUCTION**

1. Aluminium multiwire compacted conductor
2. Light-stabilized cross-linked polyethylene insulation

