



СИП-5 1x35
ТУ У 31.3-00214534-014-2002

Self-supporting wires with light-stabilized cross-linked polyethylene insulation

Used for laying:

- aerial electric power lines for the rated voltage of 0.6/1 kV
- branches to the inputs into dwellings and outbuildings

TECHNICAL SPECIFICATIONS

Rated voltage	kV	0.6 / 1
Number and rated area of phase conductors	mm ²	1 x 35
Phase insulation thickness	mm	1.3
Current ratings *		
• Continuous	A	160
• at short circuit (not more than 1 s)	kA	3.2
Maximum permissible conductor temperature		
• Continuous	°C	+90
• at short circuit (not more than 5 s)	°C	+250
Operating temperature range	°C	-60 ... +50
Permissible temperature of laying (installation), no less than	°C	-20
Minimum bending radius by laying	mm	95
Rated outer diameter of the cable (for reference) **	mm	9.5
Weight (approximate)	kg/km	130

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

* Long permissible current loads are calculated for the following conditions: ambient temperature plus 25 °C, wind speed 0.6 m/s, the intensity of solar radiation 1000 W/m²

** The external diameter may differ from the rated up to ± 10 %

CONSTRUCTION

1. Aluminium multiwire compacted conductor
2. Light-stabilized cross-linked polyethylene insulation

