




200108-011035000000



## СІПн-4 1x35 ДСТУ 4743:2007, ТУ У 27.3-00214534-079:2014

Self-supporting flame-retardant wires with polymer compound insulation

Used for laying:

- aerial electric power lines for the rated voltage of 0.6/1 kV
- branches from aerial electric power lines for the rated voltage of 0.6/1 kV to the input and for the laying on the walls of buildings and engineering structures
- in air, types II and III according to ГОСТ 15150-69

It is possible to manufacture the wire with longitudinal core sealing by water-blocking materials

Fire safety code in accordance with ДСТУ 4809:2007: ПБ100000000

Products of this mark meet the requirements:

- single wire cable flame retardance

### TECHNICAL SPECIFICATIONS

|                                                                |                 |             |
|----------------------------------------------------------------|-----------------|-------------|
| Rated voltage                                                  | kV              | 0.6 / 1     |
| Number and rated area of phase conductors                      | mm <sup>2</sup> | 1 x 35      |
| Phase insulation thickness                                     | mm              | 1.4         |
| Current ratings *                                              |                 |             |
| • Continious                                                   | A               | 160         |
| • at short circuit (not more than 1 s)                         | kA              | 3.2         |
| Maximum permissible conductor temperature                      |                 |             |
| • Continious                                                   | °C              | +90         |
| • at short circuit (not more than 5 s)                         | °C              | +250        |
| Operating temperature range                                    | °C              | -60 ... +50 |
| Permissible temperature of laying (installation), no less than | °C              | -20         |
| Minimum bending radius by laying                               | mm              | 97          |
| Rated outer diameter of the cable (for reference) **           | mm              | 9.7         |
| Weight (approximate)                                           | kg/km           | 130         |

Notes:


When ordering it is necessary to agree the factory length of the product with the manufacturer

\* Long permissible current loads are calculated for the following conditions: ambient temperature plus 25 °C, wind speed 0.6 m/s, the intensity of solar radiation 1000 W/m<sup>2</sup>

\*\* The external diameter may differ from the rated up to ± 10 %



200108-011035000000

**СІПн-4 1x35**  
**ДСТУ 4743:2007, ТУ У 27.3-00214534-079:2014**

Self-supporting flame-retardant wires with polymer compound insulation

**CONSTRUCTION****1. Aluminium multiwire compacted conductor**

*Note: It is possible to manufacture the wire with longitudinal core sealing by water-blocking materials*

**2. Flame-retardant polymer compound insulation**