

СІПн-4 4x120

ДСТУ 4743:2007, ТУ У 27.3-00214534-079:2014

Self-supporting flame-retardant wires with polymer compound insulation

Used for laying:

- aerial electric power lines for the rated voltage of 0.6/1 kV
- branches from aerial electric power lines for the rated voltage of 0.6/1 kV to the input and for the laying on the walls of buildings and engineering structures
- in air, types II and III according to ГОСТ 15150-69

It is possible to manufacture the wire with longitudinal core sealing by water-blocking materials

Fire safety code in accordance with ДСТУ 4809:2007: ПБ100000000

Products of this mark meet the requirements:

- single wire cable flame retardance

TECHNICAL SPECIFICATIONS

Rated voltage	kV	0.6 / 1
Number and rated area of phase conductors	mm ²	4 x 120
Phase insulation thickness	mm	1.7
Current ratings *		
• Continious	A	340
• at short circuit (not more than 1 s)	KA	10.9
Maximum permissible conductor temperature		
• Continious	°C	+90
• at short circuit (not more than 5 s)	°C	+250
Operating temperature range	°C	-60 ... +50
Permissible temperature of laying (installation), no less than	°C	-20
Minimum bending radius by laying	mm	390
Rated outer diameter of the cable (for reference) **	mm	39
Weight (approximate)	kg/km	1570
Rated factory cable length and gross weight of the delivery on the drums ***	m, t	# 16a: 630 • 1.2 # 18: 720 • 1.6 # 20: 1160 • 2.5

Notes:


When ordering it is necessary to agree the factory length of the product with the manufacturer

* Long permissible current loads are calculated for the following conditions: ambient temperature plus 25 °C, wind speed 0.6 m/s, the intensity of solar radiation 1000 W/m²


** The external diameter may differ from the rated up to ± 10 %



200108-014120000000

**СІПн-4 4x120**
ДСТУ 4743:2007, ТУ У 27.3-00214534-079:2014

Self-supporting flame-retardant wires with polymer compound insulation

CONSTRUCTION**1. Aluminium multiwire compacted conductor***Note: It is possible to manufacture the wire with longitudinal core sealing by water-blocking materials***2. Flame-retardant polymer compound insulation***Note: Wire lay-up is not illustrated.*