

СІПн-1 3x70+1x70+1x16
ДСТУ 4743:2007, ТУ У 27.3-00214534-066:2013

Self-supporting flame-retardant wires with polymer compound insulation, with neutral carrier non-insulated conductor

Used for laying:

- trunks of aerial electric power lines and line branches for the rated voltage of 0.6/1 kV
- in air, types I and II according to ГОСТ 15150-69

It is possible to manufacture the wire with longitudinal core sealing by water-blocking materials

Fire safety code in accordance with ДСТУ 4809:2007: ПБ100000000

Products of this mark meet the requirements:

- single wire cable flame retardance

TECHNICAL SPECIFICATIONS

Rated voltage	kV	0.6 / 1
Number and rated area of phase conductors	mm ²	3 x 70
Number and rated area of additional conductors for light circuits	mm ²	1 x 16
Carrier neutral conductor rated area	mm ²	70
Phase insulation thickness	mm	1.5
Current ratings *		
• <i>Continious</i>	A	240
• <i>at short circuit (not more than 1 s)</i>	kA	6.5
Maximum permissible conductor temperature	°C	+90
• <i>Continious</i>	°C	+250
Operating temperature range	°C	-60 ... +50
Permissible temperature of laying (installation), no less than	°C	-20
Minimum bending radius by laying	mm	356
Rated outer diameter of the cable (for reference) **	mm	35.6
Weight (approximate)	kg/km	980
Rated factory cable length and gross weight of the delivery on the drums ***	m, t	# 16a: 780 • 1.0 # 18: 890 • 1.3 # 20: 1430 • 2.0

Notes:


When ordering it is necessary to agree the factory length of the product with the manufacturer

* Long permissible current loads are calculated for the following conditions: ambient temperature plus 25 °C, wind speed 0.6 m/s, the intensity of solar radiation 1000 W/m²

** The external diameter may differ from the rated up to ± 10 %




200202-013070116700



СІПн-1 3x70+1x70+1x16
ДСТУ 4743:2007, ТУ У 27.3-00214534-066:2013

Self-supporting flame-retardant wires with polymer compound insulation, with neutral carrier non-insulated conductor

CONSTRUCTION



1. Aluminium multiwire compacted conductor

Note: It is possible to manufacture the wire with longitudinal core sealing by water-blocking materials

2. Multiwire aluminium-alloy compacted supporting conductor

Note: It is possible to manufacture the wire with longitudinal core sealing by water-blocking materials

3. Multiwire compacted aluminium assisting conductor for light circuits

4. Flame-retardant polymer compound insulation

Note: Wire lay-up is not illustrated.