



## СИПН-1 3x95+1x95 ДСТУ 4743:2007, ТУ У 27.3-00214534-066:2013

Self-supporting flame-retardant wires with polymer compound insulation, with neutral carrier non-insulated conductor

Used for laying:

- *trunks of aerial electric power lines and line branches for the rated voltage of 0.6/1 kV*
- *in air, types I and II according to ГОСТ 15150-69*

It is possible to manufacture the wire with longitudinal core sealing by water-blocking materials

Fire safety code in accordance with ДСТУ 4809:2007: ПБ100000000

Products of this mark meet the requirements:

- *single wire cable flame retardance*

### TECHNICAL SPECIFICATIONS

|  |                 |                                     |
|--|-----------------|-------------------------------------|
| Rated voltage  | kV              | 0.6 / 1                             |
| Number and rated area of phase conductors                                    | mm <sup>2</sup> | 3 x 95                              |
| Carrier neutral conductor rated area   | mm <sup>2</sup> | 95                                  |
| Phase insulation thickness   | mm              | 1.7                                 |
| Current ratings *  |                 |                                     |
| • <i>Continuous</i>  | A               | 300                                 |
| • <i>at short circuit (not more than 1 s)</i>                                | kA              | 8.8                                 |
| Maximum permissible conductor temperature                                    |                 |                                     |
| • <i>Continuous</i>  | °C              | +90                                 |
| • <i>at short circuit (not more than 5 s)</i>                                | °C              | +250                                |
| Operating temperature range  | °C              | -60 ... +50                         |
| Permissible temperature of laying (installation), no less than               | °C              | -20                                 |
| Minimum bending radius by laying   | mm              | 413                                 |
| Rated outer diameter of the cable (for reference) **                         | mm              | 41.3                                |
| Weight (approximate)   | kg/km           | 1210                                |
| Rated factory cable length and gross weight of the delivery on the drums *** | m, t            | # 18: 660 • 1.3<br># 20: 1050 • 1.9 |

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

\* Long permissible current loads are calculated for the following conditions: ambient temperature plus 25 °C, wind speed 0.6 m/s, the intensity of solar radiation 1000 W/m<sup>2</sup>

\*\* The external diameter may differ from the rated up to ± 10 %



## СИПН-1 3x95+1x95 ДСТУ 4743:2007, ТУ У 27.3-00214534-066:2013

Self-supporting flame-retardant wires with polymer compound insulation, with neutral carrier non-insulated conductor

### CONSTRUCTION

#### 1. Aluminium multiwire compacted conductor

*Note: It is possible to manufacture the wire with longitudinal core sealing by water-blocking materials*

#### 2. Multiwire aluminium-alloy compacted supporting conductor

*Note: It is possible to manufacture the wire with longitudinal core sealing by water-blocking materials*

#### 3. Flame-retardant polymer compound insulation

*Note: Wire lay-up is not illustrated.*

