

СІПн-2 3x70+1x95+2x25

ДСТУ 4743:2007, ТУ У 27.3-00214534-066:2013

Self-supporting flame-retardant wires with polymer compound insulation, with neutral carrier insulated conductor

Used for laying:

- trunks of aerial electric power lines and line branches for the rated voltage of 0.6/1 kV
- in air, types II and III according to ГОСТ 15150-69, including on sea coasts, salt lakes, in industrial areas and areas of saline sands

It is possible to manufacture the wire with longitudinal core sealing by water-blocking materials

Fire safety code in accordance with ДСТУ 4809:2007: ПБ100000000

Products of this mark meet the requirements:

- single wire cable flame retardance

TECHNICAL SPECIFICATIONS


Rated voltage	kV	0.6 / 1
Number and rated area of phase conductors	mm ²	3 x 70
Number and rated area of additional conductors for light circuits	mm ²	2 x 25
Carrier neutral conductor rated area	mm ²	95
Phase insulation thickness	mm	1.5
Current ratings *		
• <i>Continious</i>	A	240
• <i>at short circuit (not more than 1 s)</i>	kA	6.5
Maximum permissible conductor temperature		
• <i>Continious</i>	°C	+90
• <i>at short circuit (not more than 5 s)</i>	°C	+250
Operating temperature range	°C	-60 ... +50
Permissible temperature of laying (installation), no less than	°C	-20
Minimum bending radius by laying	mm	406
Rated outer diameter of the cable (for reference) **	mm	40.6
Weight (approximate)	kg/km	1220
Rated factory cable length and gross weight of the delivery on the drums ***	m, t	# 18: 720 • 1.3 # 20: 1160 • 2.1

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

* Long permissible current loads are calculated for the following conditions: ambient temperature plus 25 °C, wind speed 0.6 m/s, the intensity of solar radiation 1000 W/m²


** The external diameter may differ from the rated up to ± 10 %



СІПн-2 3x70+1x95+2x25
ДСТУ 4743:2007, ТУ У 27.3-00214534-066:2013

Self-supporting flame-retardant wires with polymer compound insulation, with neutral carrier insulated conductor

CONSTRUCTION



1. Aluminium multiwire compacted conductor

Note: It is possible to manufacture the wire with longitudinal core sealing by water-blocking materials

2. Multiwire compacted aluminium assisting conductor for light circuits

3. Multiwire aluminium-alloy compacted supporting conductor

Note: It is possible to manufacture the wire with longitudinal core sealing by water-blocking materials

4. Flame-retardant polymer compound insulation

Note: Wire lay-up is not illustrated.