



СИП-4 1x50 ДСТУ 4743:2007, ТУ У 27.3-00214534-066:2013

Self-supporting wires with light-stabilized cross-linked polyethylene insulation

Used for laying:

- aerial electric power lines for the rated voltage of 0.6/1 kV
- branches from aerial electric power lines for the rated voltage of 0.6/1 kV to the input and for the laying on the walls of buildings and engineering structures
- in air, types II and III according to ГOCT 15150-69

It is possible to manufacture the wire with longitudinal core sealing by water-blocking materials

TECHNICAL SPECIFICATIONS

Rated voltage	kV	0.6 / 1
Number and rated area of phase conductors	mm ²	1 x 50
Phase insulation thickness	mm	1.5
Current ratings *		
• Continuous	A	195
• at short circuit (not more than 1 s)	kA	4.6
Maximum permissible conductor temperature		
• Continuous	°C	+70
• at short circuit (not more than 5 s)	°C	+135
Operating temperature range	°C	-60 ... +50
Permissible temperature of laying (installation), no less than	°C	-20
Minimum bending radius by laying	mm	110
Rated outer diameter of the cable (for reference) **	mm	11
Weight (approximate)	kg/km	170
Rated factory cable length and gross weight of the delivery on the drums	m, t	# 16a: 8360 • 1.7

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

* Long permissible current loads are calculated for the following conditions: ambient temperature plus 25 °C, wind speed 0.6 m/s, the intensity of solar radiation 1000 W/m²

** The external diameter may differ from the rated up to ± 10 %



СИП-4 1x50 ДСТУ 4743:2007, ТУ У 27.3-00214534-066:2013

Self-supporting wires with light-stabilized cross-linked polyethylene insulation



CONSTRUCTION

1. Aluminium multiwire compacted conductor

Note: It is possible to manufacture the wire with longitudinal core sealing by water-blocking materials

2. Light-stabilized cross-linked polyethylene insulation