


**СІП-4 2x16**  
**ДСТУ 4743:2007, ТУ У 27.3-00214534-066:2013**

Self-supporting wires with light-stabilized cross-linked polyethylene insulation

Used for laying:

- aerial electric power lines for the rated voltage of 0.6/1 kV
- branches from aerial electric power lines for the rated voltage of 0.6/1 kV to the input and for the laying on the walls of buildings and engineering structures
- in air, types II and III according to ГОСТ 15150-69

It is possible to manufacture the wire with longitudinal core sealing by water-blocking materials

**TECHNICAL SPECIFICATIONS**

Rated voltage	kV	0.6 / 1
Number and rated area of phase conductors	mm <sup>2</sup>	2 x 16
Phase insulation thickness	mm	1.4
Current ratings *		
• <i>Continious</i>	A	100
• <i>at short circuit (not more than 1 s)</i>	kA	1.5
Maximum permissible conductor temperature		
• <i>Continious</i>	°C	+70
• <i>at short circuit (not more than 5 s)</i>	°C	+135
Operating temperature range	°C	-60 ... +50
Permissible temperature of laying (installation), no less than	°C	-20
Minimum bending radius by laying	mm	150
Rated outer diameter of the cable (for reference) **	mm	15
Weight (approximate)	kg/km	140
Rated factory cable length and gross weight of the delivery on the drums ***	m, t	# 16a: 4500 • 0.9 # 18: 5140 • 1.2 # 20: 8220 • 1.8

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

 \* Long permissible current loads are calculated for the following conditions: ambient temperature plus 25 °C, wind speed 0.6 m/s, the intensity of solar radiation 1000 W/m<sup>2</sup>


\*\* The external diameter may differ from the rated up to ± 10 %



200205-012016000000

**СІП-4 2x16**  
**ДСТУ 4743:2007, ТУ У 27.3-00214534-066:2013**

Self-supporting wires with light-stabilized cross-linked polyethylene insulation

**CONSTRUCTION****1. Aluminium multiwire compacted conductor**

*Note: It is possible to manufacture the wire with longitudinal core sealing by water-blocking materials*

**2. Light-stabilized cross-linked polyethylene insulation**

*Note: Wire lay-up is not illustrated.*