



## СИП-3-35 1x70 ДСТУ 4743:2007, ТУ У 27.3-00214534-066:2013

Single-core self-supporting high-voltage wires with light-stabilized cross-linked polyethylene insulation

Used for laying:

- *aerial electric power lines for the rated voltage from 10 kV till 35 kV*
- *in air, types II and III according to ГОСТ 15150-69, including on sea coasts, salt lakes, in industrial areas and areas of saline sands*

It is possible to manufacture the wire with longitudinal core sealing by water-blocking materials

### TECHNICAL SPECIFICATIONS

Rated voltage	kV	35
Number and rated area of phase conductors	mm <sup>2</sup>	1 x 70
Phase insulation thickness	mm	3.5
Current ratings *		
• <i>Continuous</i>	A	340
• <i>at short circuit (not more than 1 s)</i>	kA	6
Maximum permissible conductor temperature		
• <i>Continuous</i>	°C	+90
• <i>at short circuit (not more than 5 s)</i>	°C	+250
Operating temperature range	°C	-60 ... +50
Permissible temperature of laying (installation), no less than	°C	-20
Minimum bending radius by laying	mm	169
Rated outer diameter of the cable (for reference) **	mm	16.9
Weight (approximate)	kg/km	340
Rated factory cable length and gross weight of the delivery on the drums ***	m, t	# 16a: 3950 • 1.6 # 18: 4520 • 2.0 # 20: 7230 • 3.1

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

\* Long permissible current loads are calculated for the following conditions: ambient temperature plus 25 °C, wind speed 0.6 m/s, the intensity of solar radiation 1000 W/m<sup>2</sup>

\*\* The external diameter may differ from the rated up to ± 10 %



**СИП-3-35 1x70**  
**ДСТУ 4743:2007, ТУ У 27.3-00214534-066:2013**

Single-core self-supporting high-voltage wires with light-stabilized cross-linked polyethylene insulation



## CONSTRUCTION

### 1. Multiwire aluminium-alloy compacted conductor

*Note: It is possible to manufacture the wire with longitudinal core sealing by water-blocking materials*

### 2. Light-stabilized cross-linked polyethylene insulation