7, Autogennaya Str., Kharkov, 61099, Ukraine. Phone: (+38-057) 728-1244, 728-1241. Fax: (+38-057) 728-1243, (+38-0572) 946-830
E-mail: market@yuzhcable.com.ua

200301-351150000000

СИП-3-35 1х150
ДСТУ 4743:2007, ТУ У 27.3-00214534-066:2013

Single-core self-supporting high-voltage wires with light-stabilized cross-linked polyethylene insulation

Used for laying:

- *aerial electric power lines for the rated voltage from 10 kV till 35 kV*
- *in air, types II and III according to ГОСТ 15150-69, including on sea coasts, salt lakes, in industrial areas and areas of saline sands*

It is possible to manufacture the wire with longitudinal core sealing by water-blocking materials

TECHNICAL SPECIFICATIONS

Rated voltage	kV	35
Number and rated area of phase conductors	mm^2	1 x 150
Phase insulation thikness	mm	3.5
Current ratings *		
• *Continious*	A	520
• *at short circuit (not more than 1 s)*	kA	12.9
Maximum permissible conductor temperature		
• *Continious*	°C	+90
• *at short circuit (not more than 5 s)*	°C	+250
Operating temperature range	°C	-60 ... +50
Permissible temperature of laying (installation), no less than	°C	-20
Minimum bending radius by laying	mm	213
Rated outer diameter of the cable (for reference) **	mm	21.3
Weight (approximate)	kg/km	590
Rated factory cable length and gross weight of the delivery on the drums	m, t	# 16a: 2090 • 1.5 # 18: 2390 • 1.9 # 20: 3820 • 2.9

Notes:

When ordering it is neccesary to agree the factory length of the product with the manufacturer

** Long permissible current loads are calculated for the following conditions: ambient temperature plus 25 °C, wind speed 0.6 m/s, the intensity of solar radiation 1000 W/m2*

*** The external diameter may differ from the rated up to ± 10 %*

© 2024 PJSC Yuzhcable Works. © 2024 A. Kevorkyan

200301-351150000000

7, Autogennaya Str., Kharkov, 61099, Ukraine. Phone: (+38-057) 728-1244, 728-1241. Fax: (+38-057) 728-1243, (+38-0572) 946-830
E-mail: market@yuzhcable.com.ua

СИП-3-35 1х150
ДСТУ 4743:2007, ТУ У 27.3-00214534-066:2013

Single-core self-supporting high-voltage wires with light-stabilized cross-linked polyethylene insulation



CONSTRUCTION

1. Multiwire aluminium-alloy compacted conductor
2. Light-stabilized cross-linked polyethylene insulation

© 2024 PJSC Yuzhcable Works. © 2024 A. Kevorkyan