



КВБ6ШВ 19x1 ТУ У 27.3-00214534-103:2018

Control cables with copper conductors, galvanized double steel-tape armoured, with PVC compound insulation, PVC compound protection hose

Cables are used for laying:

- in premises, dry ducts and tunnels, in corrosive environment
- single laying
- in places, where small mechanical impacts on cable are possible, including tensile forces

Manufacturing of cable with polyethylene inner sheath is possible

Manufacturing of non-galvanized armoured cable, covered with a layer of bitumen and PET film is possible

Fire safety code in accordance with ДСТУ 4809:2007: ПБ100000000

Products of this mark meet the requirements:

- single wire cable flame retardance

TECHNICAL SPECIFICATIONS

Rated voltage (AC / DC)	V	660 / 1000
Number and rated area of conductors	mm ²	19 x 1
Minimum bending radius by laying	mm	200
Cable outer diameter (for reference only) **	mm	20
Cable weight (approximate)	kg/km	700
Rated factory cable length and gross weight of the delivery on the drums	m, t	# 12: 820 • 0.7 # 14: 1570 • 1.3

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

** The external diameter may differ from the rated up to $\pm 10\%$

CONSTRUCTION

1. Copper conductor
2. PVC compound insulation
3. PET film winding
4. PVC compound belt insulation

Note: Manufacturing of cable with polyethylene inner sheath is possible

5. Double galvanized steel-tape armour

Note: Manufacturing of non-galvanized armoured cable, covered with a layer of bitumen and PET film is possible

6. Pressed PVC compound protection hose

Note: Conductor twisting is not illustrated

