**СБВБ6ШВнг 24х1**  
**ТУ У 31.3-00214534-008-2001**

Signal blocking cables with copper conductors, with polyethylene insulation, in low flammable PVC compound sheath, with galvanized double-steel-tape armouring, in low flammable PVC compound hose

Designed for electrical installations of railway signaling, centralization, blocking and automation at a rated voltage of 380 V AC at frequency 50 Hz or 700 V DC

Cables are used for laying:

- *in bunches*
- *in dry cable duct system, tunnels, collectors in corrosive environment*
- *in places, where small mechanical impacts on cable are possible, including tensile forces*

Fire safety code in accordance with ДСТУ 4809:2007: ПБ121000000

Products of this mark meet the requirements:

- *single wire cable flame retardance*
- *bunched cable flame retardance category A*
- *toxicity class Tk1 of the combustion products of nonmetallic elements (toxicity index from 13 up to 40 g/m<sup>3</sup>)*


**TECHNICAL SPECIFICATIONS**

|  |        |                 |
|--|--------|-----------------|
| Rated voltage  | V      | 380 / 700       |
| Number and rated diameter of conductors                                      | mm     | 24 x 1          |
| Electrical resistance of the conductor at 20 °C                              | Ohm/km | 23.3            |
| Operating capacity, not more than  | nF/km  | 150.0           |
| Operating temperature range  | °C     | -40 ... +60     |
| Minimum bending radius by laying   | mm     | 228             |
| Cable outer diameter (for reference only) **                                 | mm     | 19              |
| Cable weight (approximate)   | kg/km  | 611             |
| Rated factory cable length and gross weight of the delivery on the drums *** | m, t   | # 12: 910 • 0.7 |

Notes:

*When ordering it is necessary to agree the factory length of the product with the manufacturer*

*\*\* The external diameter may differ from the rated up to ± 10 %*



## **СБВБШВнг 24х1** **ТУ У 31.3-00214534-008-2001**

Signal blocking cables with copper conductors, with polyethylene insulation, in low flammable PVC compound sheath, with galvanized double-steel-tape armouring, in low flammable PVC compound hose

### **CONSTRUCTION**

1. Copper conductor
2. Polyethylene insulation
3. PET film winding
4. Low-flammable PVC compound inner sheath
5. Double galvanized steel-tape armour
6. Low-flammable PVC compound protection hose

*Note: Conductor twisting is not illustrated*

