**СБЗПБ6Шв 19х2х1**
ТУ У 31.3-00214534-008-2001

Signal blocking cables with copper conductors, with polyethylene insulation, with water-blocking core filling, in polyethylene sheath, with galvanized double-steel-tape armouring, in PVC compound hose

Designed for electrical installations of railway signaling, centralization, blocking and automation at a rated voltage of 380 V AC at frequency 50 Hz or 700 V DC

Cables are used for laying:

- *in ducts, tunnels, collectors, in soil (trenches), in corrosive environment*
- *in conditions of excessive humidity*
- *in places, where small mechanical impacts on cable are possible, including tensile forces*

Fire safety code in accordance with ДСТУ 4809:2007: ПБ100000000

Products of this mark meet the requirements:

- *single wire cable flame retardance*


TECHNICAL SPECIFICATIONS

| | | |
|---|--------|-----------------|
| Rated voltage | V | 380 / 700 |
| Number of pairs and nominal conductor diameter | | 19 x 1 |
| Electrical resistance of the conductor at 20 °C | Ohm/km | 28.8 |
| Operating capacity, not more than | nF/km | 100.0 |
| Attenuation coefficient of pairs at a temperature of 20 °C, not more than | dB/km | 0.94 |
| Coupling losses on near-end of cable between any pairs over a length of 300 m, not less than: | | |
| • <i>for 100% of the values</i> | dB | 60.0 |
| • <i>for 80% of the values</i> | dB | 62.0 |
| Operating temperature range | °C | -50 ... +60 |
| Minimum bending radius by laying | mm | 300 |
| Cable outer diameter (for reference only) ** | mm | 25 |
| Cable weight (approximate) | kg/km | 923 |
| Rated factory cable length and gross weight of the delivery on the drums *** | m, t | # 14: 930 • 1.0 |

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

*** The external diameter may differ from the rated up to $\pm 10\%$*



СБЗПБ6Шв 19x2x1 **ТУ У 31.3-00214534-008-2001**

Signal blocking cables with copper conductors, with polyethylene insulation, with water-blocking core filling, in polyethylene sheath, with galvanized double-steel-tape armouring, in PVC compound hose

CONSTRUCTION

1. Copper conductor
2. Polyethylene insulation
3. Water-blocking filling
4. Polyethylene inner sheath
5. Double galvanized steel-tape armour
6. PVC compound protection hose

Note: Pair twisting in the layer of core on the picture not shown.

