



СБЗПБ6Шп 24x1 ТУ У 31.3-00214534-008-2001

Signal blocking cables with copper conductors, with polyethylene insulation, with water-blocking core filling, in polyethylene sheath, with galvanized double-steel-tape armouring, in polyethylene hose

Designed for electrical installations of railway signaling, centralization, blocking and automation at a rated voltage of 380 V AC at frequency 50 Hz or 700 V DC

Cables are used for laying:

- in soil (trenches), in corrosion environment
- in conditions of excessive humidity
- in places, where small mechanical impacts on cable are possible, including tensile forces

TECHNICAL SPECIFICATIONS

Rated voltage	V	380 / 700
Number and rated diameter of conductors	mm	24 x 1
Electrical resistance of the conductor at 20 °C	Ohm/km	23.3
Operating capacity, not more than	nF/km	150.0
Operating temperature range	°C	-50 ... +60
Minimum bending radius by laying	mm	240
Cable outer diameter (for reference only) **	mm	20
Cable weight (approximate)	kg/km	547
Rated factory cable length and gross weight of the delivery on the drums ***	m, t	# 12: 820 • 0.6 # 14: 1570 • 1.0

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

** The external diameter may differ from the rated up to $\pm 10\%$

CONSTRUCTION

1. Copper conductor
2. Polyethylene insulation
3. Water-blocking filling
4. Polyethylene inner sheath
5. Double steel-tape armour
6. Bitumen layer
7. Polyethylene protection hose

Note: Conductor twisting is not illustrated

