



NHXMH-O 3x25 DIN VDE 0250-214

Power cables with copper conductors, XLPE-insulated, with halogen-free polymer compound outer sheath

Cables are used for:

- electric wiring and cable lines installation in industrial, residential and public buildings and facilities
- laying over the plaster, inside and under plaster, in brick masonry and concrete, in pipes and ducts
- wiring in office premises equipped with computer and microprocessor equipment, in kindergartens, schools, hospitals, for cable lines of entertainment complexes and sports facilities
- outdoor installation, if protected from sun rays

Manufacturing of cables with light-stabilized outer sheath is possible

Fire safety code in accordance with ДСТУ 4809:2007: ПБ123122000

Products of this mark meet the requirements:

- single wire cable flame retardance
- bunched cable flame retardance category A
- toxicity class Tk3 of the combustion products of nonmetallic elements (toxicity index over 120 g/m³)
- class ДТк1 on smoke-forming ability by smouldering of non-metallic elements (coefficient of smoke formation from 50 to 500 m²/kg)
- class ДПк2 on smoke-forming ability by combustion (minimum luminous flux more than 60 %)
- corrosive class Kk2 of combustion products of non-metallic elements (the number of halogen hydrides less than 150 mg/g, pH more than 4.3, specific conductivity less than 10 μS/mm)

TECHNICAL SPECIFICATIONS

| | | |
|--|-----------------|------------------|
| Rated voltage | kV | 0.66 |
| Number and rated area of conductors | mm ² | 3 x 25 |
| Insulation thickness | mm | 0.9 |
| Permissible continuous current rating * | | |
| • by aerial laying (AC of industrial frequency) * | A | 141 |
| • by burial (AC of industrial frequency) * | A | 144 |
| Operating temperature range | °C | -50 ... +50 |
| Minimum bending radius by laying | mm | 92.4 |
| Rated outer diameter of the cable (for reference) ** | mm | 23.1 |
| Cable weight (approximate) | kg/km | 1230 |
| Rated factory cable length and gross weight of the delivery on the drums *** | m, t | # 14: 1090 • 1.5 |

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

* Long permissible current loads are calculated for the following conditions: air temperature plus 25 °C, soil temperature plus 15 °C, thermal resistivity of soil 1.2 °K·m/W, laying depth in the soil 0.7 m

** The external diameter may differ from the rated up to ± 10 %



NHXMH-O 3x25 **DIN VDE 0250-214**

Power cables with copper conductors, XLPE-insulated, with halogen-free polymer compound outer sheath

CONSTRUCTION

1. *Copper multiwire conductor*
 2. *XLPE insulation*
 3. *Halogen-free polymer compound inner sheath*
 4. *Outer sheath of halogen-free polymer composition*
- Note: Manufacturing of cables with light-stabilized outer sheath is possible*

