







# АПВнг 1 x 70 ТУ У 31.3-00214534-056:2006

Installation wires with aluminium conductors, low flammable PVC compound insulation

### Used for:

- fixed laying in lighting and power circuits and also for electric equipment, machines, mechanisms and machine tools installation for rated voltage up to 450 V (for networks up to 450/750), frequency up to 100 Hz or constant voltage of 1000 V
- for laying in steel pipes, hollow ducts of building structures, on trays, etc.

Manufacturing of wires in climate version F and T is possible

Fire safety code in accordance with ДСТУ 4809:2007: ΠБ140000000

Products of this mark meet the requirements:

- · single wire cable flame retardance
- · bunched cable flame retardance category C

# **TECHNICAL SPECIFICATIONS**

Rated voltage	kV	0.45
Number and rated area of conductors	mm²	1 x 70
Insulation thikness	mm	1.4
Operating temperature range	°C	-40 +50
Flexibility class acc. to ΓΟCT 22483-77		2
Minimum bending radius by laying	mm	128
Outer diameter (nominal, for reference only)	mm	12.8
Outer diameter (maximum, for reference only)	mm	15
Weight (approximate)	kg/km	256

### Notes:

When ordering it is neccesary to agree the factory length of the product with the manufacturer

# 2

## CONSTRUCTION

- 1. Aluminium multiwire conductor
- 2. Low-flammable PVC compound insulation