

## АПВнгд 1 x 95 ТУ У 31.3-00214534-056:2006

Installation wires with aluminium conductors, low fire-risk PVC compound insulation

Used for:

- *fixed laying in lighting and power circuits and also for electric equipment, machines, mechanisms and machine tools installation for rated voltage up to 450 V (for networks up to 450/750), frequency up to 100 Hz or constant voltage of 1000 V*
- *for laying in steel pipes, hollow ducts of building structures, on trays, etc.*

Manufacturing of wires in climate version F and T is possible

Fire safety code in accordance with ДСТУ 4809:2007: ПБ123121000

Products of this mark meet the requirements:


- *single wire cable flame retardance*
- *bunched cable flame retardance category A*
- *toxicity class Tk3 of the combustion products of nonmetallic elements (toxicity index over 120 g/m<sup>3</sup>)*
- *class ДТк1 on smoke-forming ability by smouldering of non-metallic elements (coefficient of smoke formation from 50 to 500 m<sup>2</sup>/kg)*
- *class ДПк2 on smoke-forming ability by combustion (minimum luminous flux more than 60 %)*
- *corrosive class Кк1 of combustion products of non-metallic elements (the number of halogen hydrides less than 150 mg/g, pH less than 4.3, specific conductivity more than 10 μS/mm)*

### TECHNICAL SPECIFICATIONS

|  |                 |                  |
|--|-----------------|------------------|
| Rated voltage  | kV              | 0.45             |
| Number and rated area of conductors  | mm <sup>2</sup> | 1 x 95           |
| Insulation thickness   | mm              | 1.6              |
| Operating temperature range  | °C              | -40 ... +50      |
| Flexibility class acc. to ГОСТ 22483-77                                      |                 | 2                |
| Minimum bending radius by laying   | mm              | 146              |
| Outer diameter (nominal, for reference only)                                 | mm              | 14.6             |
| Outer diameter (maximum, for reference only)                                 | mm              | 17               |
| Weight (approximate)   | kg/km           | 350              |
| Rated factory cable length and gross weight of the delivery on the drums *** | m, t            | # 10: 1210 • 0.5 |

Notes:

*When ordering it is necessary to agree the factory length of the product with the manufacturer*



**АПВнгд 1 х 95**  
**ТУ У 31.3-00214534-056:2006**

Installation wires with aluminium conductors, low fire-risk PVC compound insulation

**CONSTRUCTION**

1. Aluminium multiwire conductor
2. Low fire-risk PVC compound insulation

