



АПВнгд 1 x 120 ТУ У 31.3-00214534-056:2006

Installation wires with aluminium conductors, low fire-risk PVC compound insulation

Used for:

- *fixed laying in lighting and power circuits and also for electric equipment, machines, mechanisms and machine tools installation for rated voltage up to 450 V (for networks up to 450/750), frequency up to 100 Hz or constant voltage of 1000 V*
- *for laying in steel pipes, hollow ducts of building structures, on trays, etc.*

Manufacturing of wires in climate version F and T is possible

Fire safety code in accordance with ДСТУ 4809:2007: ПБ123121000

Products of this mark meet the requirements:


- *single wire cable flame retardance*
- *bunched cable flame retardance category A*
- *toxicity class Tk3 of the combustion products of nonmetallic elements (toxicity index over 120 g/m³)*
- *class ДТк1 on smoke-forming ability by smouldering of non-metallic elements (coefficient of smoke formation from 50 to 500 m²/kg)*
- *class ДПк2 on smoke-forming ability by combustion (minimum luminous flux more than 60 %)*
- *corrosive class Кк1 of combustion products of non-metallic elements (the number of halogen hydrides less than 150 mg/g, pH less than 4.3, specific conductivity more than 10 μS/mm)*

TECHNICAL SPECIFICATIONS

| | | |
|--|-----------------|-------------------------------------|
| Rated voltage | kV | 0.45 |
| Number and rated area of conductors | mm ² | 1 x 120 |
| Insulation thickness | mm | 1.6 |
| Operating temperature range | °C | -40 ... +50 |
| Flexibility class acc. to ГОСТ 22483-77 | | 2 |
| Minimum bending radius by laying | mm | 162 |
| Outer diameter (nominal, for reference only) | mm | 16.2 |
| Outer diameter (maximum, for reference only) | mm | 19 |
| Weight (approximate) | kg/km | 428 |
| Rated factory cable length and gross weight of the delivery on the drums | m, t | # 10: 930 • 0.5 # 12: 1280 • 0.7 |

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer



АПВнгд 1 x 120
ТУ У 31.3-00214534-056:2006

Installation wires with aluminium conductors, low fire-risk PVC compound insulation

CONSTRUCTION

1. Aluminium multiwire conductor
2. Low fire-risk PVC compound insulation

