



## ПВ2нг 1 x 10 TY Y 31.3-00214534-056:2006

Installation flat wires with copper conductors, low flammable PVC compound insulation

Used for:

- fixed laying in lighting and power circuits and also for electric equipment, machines, mechanisms and machine tools installation for rated voltage up to 450 V (for networks up to 450/750), frequency up to 100 Hz or constant voltage of 1000 V
- electric subcircuits installation, where wire-bending are possible

Manufacturing of wires in climate version F and T is possible

Fire safety code in accordance with ДСТУ 4809:2007: ПБ120000000

Products of this mark meet the requirements:

- single wire cable flame retardance
- bunched cable flame retardance category A

### TECHNICAL SPECIFICATIONS

|  |                 |             |
|--|-----------------|-------------|
| Rated voltage                                | kV              | 0.45        |
| Number and rated area of conductors          | mm <sup>2</sup> | 1 x 10      |
| Insulation thickness                         | mm              | 1           |
| Operating temperature range                  | °C              | -40 ... +50 |
| Flexibility class acc. to ГОСТ 22483-77      |                 | 2           |
| Minimum bending radius by laying             | mm              | 30.5        |
| Outer diameter (nominal, for reference only) | mm              | 6.1         |
| Outer diameter (maximum, for reference only) | mm              | 6.8         |
| Weight (approximate)                         | kg/km           | 116         |

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

### CONSTRUCTION

1. Copper multiwire conductor
2. Low-flammable PVC compound insulation

