



ШБВП 2 x 0.75 ТУ У 31.3-00214534-059:2008

Connecting flat cords with copper conductors, PVC compound insulation, PVC compound outer sheath

Used for:

- laying in dry and damp areas, for installation in switchboards, in ducts, for concealed and open wiring on the walls, in the networks for AC voltage up to 380 V (for systems up to 380/660 V)
- electric subcircuits installation , where frequent wire-bending are possible

Fire safety code in accordance with ДСТУ 4809:2007: ПБ100000000

Products of this mark meet the requirements:

- single wire cable flame retardance

TECHNICAL SPECIFICATIONS

| | | |
|---|-----------------|-------------|
| Rated voltage | kV | 0.38 |
| Number and rated area of conductors | mm ² | 2 x 0.75 |
| Insulation thickness | mm | 0.5 |
| Permissible continuous current by aerial laying | A | 6 |
| Operating temperature range | °C | -15 ... +50 |
| Flexibility class acc. to ГОСТ 22483-77 | | 4 |
| Minimum bending radius by laying | mm | 27 |
| Width and thickness (rated, for reference only) | mm | 5.4 x 3.3 |
| Weight (approximate) | kg/km | 33 |

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

CONSTRUCTION

1. Copper multiwire conductor
2. PVC compound insulation
3. PVC compound outer sheath

