



ПВВПнг 3 x 6 ТУ У 31.3-00214534-059:2008

Connecting flat wires with copper conductors, PVC compound insulation, low flammable PVC compound outer sheath

Used for:

- *laying in dry and damp areas, for installation in switchboards, in ducts, for concealed and open wiring on the walls, in the networks for AC voltage up to 380 V (for systems up to 380/660 V)*

Fire safety code in accordance with ДСТУ 4809:2007: ПБ120000000

Products of this mark meet the requirements:

- *single wire cable flame retardance*
- *bunched cable flame retardance category A*

TECHNICAL SPECIFICATIONS

Rated voltage	kV	0.38
Number and rated area of conductors	mm ²	3 x 6
Insulation thickness	mm	0.7
Permissible continuous current by aerial laying	A	40
Operating temperature range	°C	-15 ... +50
Flexibility class acc. to ГОСТ 22483-77		1
Minimum bending radius by laying	mm	72
Width and thickness (rated, for reference only)	mm	14.4 x 6.3
Weight (approximate)	kg/km	246
Rated factory cable length and gross weight of the delivery on the drums ***	m, t	# 10: 1210 • 0.4

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

CONSTRUCTION

1. *Copper conductor*
2. *PVC compound insulation*
3. *Low flammable PVC compound outer sheath*

