7, Autogennaya Str., Kharkov, 61099, Ukraine. Phone: (+38-057) 728-1244, 728-1241. Fax: (+38-057) 728-1243, (+38-0572) 946-830
E-mail: market@yuzhcable.com.ua

280401-066001005000

ВПВ 1 х 50
ТУ 16.705.077-79, ТУ У 27.3-00214534-037:2013

Installation wires for water submersible electric motors, with copper conductors, polyethylene insulation, PVC compound outer sheath

Used for:

- *operation under pressure up to 7 MPa (70 kgf/cm^2)*

Fire safety code in accordance with ДСТУ 4809:2007: ПБ100000000
Products of this mark meet the requirements:

- *single wire cable flame retardance*

TECHNICAL SPECIFICATIONS

Rated voltage	kV	0.66
Number and rated area of conductors	mm^2	1 x 50
Insulation thikness	mm	1.4
Operating temperature range	˚C	-40 ... +65
Minimum bending radius by laying	mm	155
Outer diameter (nominal, for reference only)	mm	15.5
Weight (approximate)	kg/km	590
Rated factory cable length and gross weight of the delivery on the drums ***	m, t	# 10: 1060 • 0.7 # 12: 1450 • 1.0

Notes:

When ordering it is neccesary to agree the factory length of the product with the manufacturer



CONSTRUCTION

1. *Copper multiwire conductor*
2. *Polyethylene insulation*
3. *PVC compound outer sheath*

© 2024 PJSC Yuzhcable Works. © 2024 A. Kevorkyan