7, Autogennaya Str., Kharkov, 61099, Ukraine. Phone: (+38-057) 728-1244, 728-1241. Fax: (+38-057) 728-1243, (+38-0572) 946-830
E-mail: market@yuzhcable.com.ua

300501-100001000100

ППІ-А 1х1
ТУ У 31.3-00214534-015-2003

Copper wires in kapton insulation

Designed to manufacture control cable sealed cable modules and other equipment, for AC and DC circuits, voltage up to 1000 V, for systems NPP class 2О, 3L

Fire safety code in accordance with ДСТУ 4809:2007: ПБ100000000
Products of this mark meet the requirements:
- *single wire cable flame retardance*

TECHNICAL SPECIFICATIONS

Rated voltage	kV	1
Number and rated area of conductors	mm^2	1 x 1
Heat-resistance class		200 (200 °C)
Minimum permissible environment temperature	°C	-60
Rated outer diameter of the cable (for reference) **	mm	1.61

Notes:

*** The external diameter may differ from the rated up to ± 10 %*



CONSTRUCTION

1. Copper conductor
2. Polyimide-fluoroplastic film winding
3. Polyimide-fluoroplastic film winding

© 2024 PJSC Yuzhcable Works. © 2024 A. Kevorkyan