



## ОП \* 10 – 2.7 ТУ У 31.3-00214534-036-2004

### Fiber optic module-core cables with polyethylene outer sheath

---

#### Mark formation:

ОП-[a]-[b] [c]10(10x[e])-2.7

[a] central strength element

- C – steel
- No marks – dielectric

[b] quantity of optical fibers in the cable, possible values

- 60, 80, 100, 120, 130, 140, 150, 160

[c] type of optical fiber

- E – single-mode (ITU-T G.652B)
- A – single-mode with extended wavelength band (ITU-T G.652D, ITU-T G.657A1)
- C – single-mode with non-zero shifted dispersion (ITU-T G.655)
- M – multimode with core and sheath diameter ratio 50 : 125 mm (ITU-T G.651)
- B – multimode with core and sheath diameter ratio 62.5 : 125 mm (IEC 60793-2)

[e] quantity of optical fibers in the module:

- 1 ... 16
- 

Manufacturing of cables in climate version F is possible

Manufacturing of cables with steel strength element is possible

Manufacturing of cables, sealed with alumopolymer tape is possible (for laying in partially flooded premises)

It is possible to manufacture cables with gel-filled core or dry core (with water-blocking yarns and tapes)

It is possible to manufacture cables with a number of core elements up to and including 18

---

Order placing: sample of indication (corresponds to configuration pattern)

ОП-100A10(10x10)-2.7 • ТУ У 31.3-00214534-036-2004

---

Cables are used for:

- installation in cable ducts, blocks, pipes, protection polyethylene pipes (including air installation method), without risk of damage by rodents



**ОП \* 10 – 2.7**  
**ТУ У 31.3-00214534-036-2004**

Fiber optic module-core cables with polyethylene outer sheath

**TECHNICAL SPECIFICATIONS**

|  |           |                                       |
|--|-----------|---------------------------------------|
| Number of cable core elements  | units     | 10                                    |
| Number of optical fibers in cable  | units     | 60 ... 160                            |
| Electrical resistance of sheath insulation, not less than                            | MOhm · km | 2000                                  |
| Permissible tensile force  | kN        | 2.7                                   |
| Permissible crushing force, no less than   | N/10 sm   | 3000                                  |
| Operating temperature range  | °C        | -40 ... +60                           |
| Operating temperature range (in climate version F)                                   | °C        | -60 ... +60                           |
| Cable weight (approximate, depending on construction)                                | kg/km     | 150 ... 185                           |
| Rated outer diameter of the cable (for reference only, depending on construction) ** | mm        | 14 ... 16                             |
| Minimum bending radius during laying   | mm        | 320                                   |
| Rated factory cable length and gross weight of the delivery on the drums ***         | m, t      | # 12a: 2060 · 0.4<br># 14: 2790 · 0.6 |

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

\*\* The external diameter may differ from the rated up to  $\pm 10\%$

**CONSTRUCTION**

**1. Central dielectric strength element**

Note: Manufacturing of cables with steel strength element is possible

**2. Optic fibers**

**3. Tube of fiber optic module**

**4. PET film winding**

**5. Polyethylene outer sheath**

Notes:

- Optical module twisting is not illustrated.
- Manufacturing of cables, sealed with alumopolymer tape is possible (for laying in partially flooded premises)
- It is possible to manufacture cables with gel-filled core or dry core (with water-blocking yarns and tapes)
- It is possible to manufacture cables with a number of core elements up to and including 18

