



Micro Tube-HF 12 * (1x12)-1 TY Y 27.3-00214534-116:2019

Fiber optic distribution cables of micro-tube construction with flame-retardant, halogen-free and low smoking (HFFR) polymer compound sheath

Mark formation:

Micro Tube-HF 12[c](1x12)-1

[c] type of optical fiber

- *A – single-mode with extended wavelength band (ITU-T G.652D, ITU-T G.657A1)*
- *D – single-mode, not sensitive to losses on macro-bending (ITU-T G.657A2)*

Order placing: sample of indication

Micro Tube-HF 12A(1x12)-1

Cable construction provides fast access to micro-tubes and fibres (no tools required), minimum of sealing compound and avoiding the risk of micro-tube kinking

Cables are used for:

- *for digital signal transmission in optic local networks as distribution cables*
- *for compact outdoor installation in PE ducts by pulling or floating techniques*
- *in areas with exclusive fire safety requirements*

Fire safety code in accordance with ДСТУ 4809:2007: ПБ103122000

Products of this mark meet the requirements:

- *single wire cable flame retardance*
- *toxicity class Tk3 of the combustion products of nonmetallic elements (toxicity index over 120 g/m³)*
- *class ДТк1 on smoke-forming ability by smouldering of non-metallic elements (coefficient of smoke formation from 50 to 500 m²/kg)*
- *class ДПк2 on smoke-forming ability by combustion (minimum luminous flux more than 60 %)*
- *corrosive class Kк2 of combustion products of non-metallic elements (the number of halogen hydrides less than 150 mg/g, pH more than 4.3, specific conductivity less than 10 μS/mm)*



Micro Tube-HF 12 * (1x12)-1 TY Y 27.3-00214534-116:2019

Fiber optic distribution cables of micro-tube construction with flame-retardant, halogen-free and low smoking (HFFR) polymer compound sheath

TECHNICAL SPECIFICATIONS

| | | |
|--|---------|-------------|
| Number of optical micro-tube in cable | | 1 |
| Number of optical fibers in cable | units | 12 |
| Permissible tensile force (short-term) | N | 1000 |
| Permissible tensile force (continuous) | N | 500 |
| Permissible crushing force, no less than | N/10 sm | 1500 |
| Ambient temperature | | |
| • during operation | °C | -30 ... +70 |
| • during storage and transportation | °C | -30 ... +70 |
| • during laying and installation | °C | -10 ... +40 |
| Cable weight (approximate) | kg/km | 50 |
| Rated outer diameter of the cable (for reference) ** | mm | 7.7 |
| Minimum bending radius during laying | mm | 154 |
| Minimum bending radius during operation | mm | 77 |

Notes:

When ordering it is necessary to agree the factory length of the product with the manufacturer

** The external diameter may differ from the rated up to $\pm 10\%$

CONSTRUCTION

1. Fiberglass rod in sheath
2. Optic fibers
3. Tube of fiber optic micromodule
4. Aramid-thread or glass-thread layer
5. Lapping layer of water-blocking tape
6. Outer sheath of halogen-free flame retardant polymer composition with low smoke emission

